

Variable Speed Drive Cables (VSD)

Application:	Supply motors from variable speed controllers in fixed installations. Cables can be laid unenclosed, enclosed in conduit, mounted on tray, or in underground ducts, where they are subject to mechanical damage. Designed to significantly reduce radiated interference from electrical noise.
Conductor:	3C - Plain Annealed Copper Conductor Class 5 3C+3E - Plain Annealed Copper Conductor Class 2
Insulation:	3C - PVC V-90HT 3C+3E - XLPE
Core Colours:	2C+E - Black Blue, Green/Yellow 3C+3E - Black, Blue, Brown, Green/Yellow + Numbered
Screen:	3C - Tinned Copper Braided 3C+3E - Copper Tape
Bedding:	PVC
Sheath:	3C - PVC CLEAR 3C+3E - 5V-90 PVC BLACK
Armour:	Galvanised Steel Wire
Standards:	AS/NZS 5000.1, AS1125 (Conductor), AS/NZS 3808 (PVC)
Greenstar:	Approved

2 Core + Earth

ELECTRA Part Number	SIZE	Main Core Insulation	Earth Core Insulation	SHEATH Thickness	O.D.
VSD2015E	1.5	0.8	0.8	1.8	11.2
VSD2025E	2.5	0.8	0.8	1.8	12.5
VSD2040E	4	1.0	0.8	1.8	14.0

*Size = mm²; O.D. ± 10%; Main Core Insulation, Earth Core Insulation, Sheath Thickness & O.D. = mm

3 Core + Earth

ELECTRA Part Number	SIZE	Main Core Insulation	Earth Core Insulation	SHEATH Thickness	O.D.
VSD3015E	1.5	0.8	0.8	1.8	12.0
VSD3025E	2.5	0.8	0.8	1.8	13.4
VSD3040E	4	1.0	0.8	1.8	15.2
VSD3060E	6	1.0	0.8	1.8	16.7
VSS3100E	10	1.0	1.0	1.8	19.8
VSD3160E	16	1.0	1.0	1.8	22.5
VSD3250E	25	1.2	1.0	1.8	26.3
VSD3350E	35	1.2	1.0	1.9	29.3
VSD3500E	50	1.4	1.0	2.1	34.2
VSD3700E	70	1.4	1.2	2.2	38.9
VSD3950E	95	16.0	1.2	2.3	42.9

*Size = mm²; O.D. ± 10%; Main Core Insulation, Earth Core Insulation, Sheath Thickness & O.D. = mm

3 Core + 3 Earth

ELECTRA Part Number	SIZE	Main Core Insulation	Earth Core Insulation	SHEATH Thickness	O.D.
VSD3025+3E	2.5	0.7	0.7	1.8	14.5
VSD3040+3E	4	0.7	0.7	1.8	16.5
VSD3060+3E	6	0.7	0.7	1.8	17.3
VSS3100+3E	10	0.7	0.7	1.8	18.5
VSD3160+3E	16	0.7	0.7	1.8	20.6
VSD3250+3E	25	0.9	0.7	1.8	24.5
VSD3350+3E	35	0.9	0.7	1.9	26.5
VSD3500+3E	50	1.0	0.7	2.1	29.5
VSD3700+3E	70	1.1	0.7	2.2	34.5
VSD3950+3E	95	1.1	0.7	2.3	39.0

*Size = mm²; O.D. ± 10%; Main Core Insulation, Earth Core Insulation, Sheath Thickness & O.D. = mm

electracables.com.au

SYDNEY
(02) 8786 5200

MELBOURNE
(03) 9706 6819

BRISBANE
(07) 3386 9800

PERTH
(08) 9454 2628

The information provided herein is indicative only. It is not a representation or warranty provided by Electra Cables (Aust) Pty Ltd ("Electra") for the suitability of a product for a particular purpose. Electra may, without notice, change and/or update its products to ensure compliance with the relevant Australian Standards. Electra are not liable for any reliance made on the information provided herein or the installation of Electra products unless otherwise agreed by Electra. All rights reserved. ABN 38 056 024 38