



Outdoor Isolator Switches Weatherproof Range

The Hippo - Weatherproof Isolator Switches are ready for all Australian conditions where installations are exposed to a variety of tough environments.











Available Now through your Electrical Wholesaler



The Trader Hippo Weatherproof Isolators are ready for use by Australian Electrical Contractors.

Australia has harsh climatic conditions and the Hippo is ready to tough it out in sun or rain or in any environment where switchgear needs enduring protection from the elements.

Nearly every job requires a weatherproof isolator either in residential, commercial or industrial applications.

Weatherproof Isolators are used frequently for installations around:

Air Conditioners

Solar

Swimming Pools

Carparks

Garden Areas

Exterior Walls

And the list goes on.

Hippo Weatherproof Isolator Switches switch firmly, to ensure they are in the ON or OFF position with confidence.

Features include:

- Combination head terminal screws
- Combination head earth and neutral terminal screws
- Alignment sleeves on switch housing guides screwdriver into terminal screws, reduces screwdriver tips jumping out.

Outdoor Illuminated Signage







Example of internal 4-pole switch

| Hippo Isolator part number | No. of poles | Current rating | Voltage | Utilization category | Motor Rating | IP Rating | Top Entries | Bottom Entries | Terminal screw drive | Terminal hole size | Padlock hole | Width | Height | Depth | |
|----------------------------|----------------------|----------------|---------|----------------------|-----------------|--------------|----------------------|----------------------|--------------------------|--------------------|--------------|-------|---------|--------|--|
| HPISW120 | 1 | 20A | 250V ac | _ | M100 | IP65 | 2 x 25mm Plain | 2 x 20mm Plain | #1 Philips/Flat combo | Dia 4.5mm | 8.4mm | 84mm | 84mm | 83mm | |
| HPISWL120 | 1 | 20A | 250V ac | - | M220 | IP65 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 6.5mm | 8.4mm | 84mm | 164mm | 84mm | |
| HPISWL140 | 1 | 40A | 250V ac | _ | M220 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 6.5mm | 8.4mm | 84mm | 164mm | 84mm | |
| HPISWL163 | 1 | 63A | 250V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL220 | 2 | 20A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL235 | 2 | 35A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL263 | 2 | 63A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL320 | 3 | 20A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL335 | 3 | 35A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL363 | 3 | 63A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL420 | 4 | 20A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL435 | 4 | 35A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| HPISWL463 | 4 | 63A | 440V ac | AC-22A | M180 | IP66 | 2 x 25mm Threaded | 2 x 25mm Threaded | #2 Philips/Flat combo | Dia 7.7mm | Dia 9.4mm | 82mm | 168.5mm | 86.5mm | |
| | HEAVY DUTY ISOLATORS | | | | | | | | | | | | | | |
| Hippo Isolator part number | No. of poles | Current rating | Voltage | Utilization category | Motor Rating | IP Rating | Top Entries | Bottom Entries | Terminal screw drive | Terminal hole size | Padlock hole | Width | Height | Depth | |
| HPISW220 | 2 | 20A | 250V ac | AC23A | M160 | IP66 | 2 x 25mm Plain | 2 x 20mm Plain | #1 Philips/Flat combo | Dia 4.5mm | 8.2mm | 84mm | 84mm | 83mm | |
| HPISW240 | 2 | 40A | 250V ac | AC23A | M220 | IP66 | 2 x 25mm Plain | 2 x 20mm Plain | #1 Philips/Flat combo | Dia 6.4mm | 8.2mm | 84mm | 84mm | 83mm | |







BLACK SINGLE POLE









THREE POLE











