



 PRODUCT-DETAILS

ACS580-01-026A-4+B056

LV AC general purpose wall-mounted drive,
IEC: Pn 11 kW, 25 A, 400 V (ACS580-01-026A-
4+B056)



General Information

Global Commercial Alias	ACS580-01-026A-4+B056
Product ID	3AXD50000038977
ABB Type Designation	ACS580-01-026A-4+B056
EAN	6438177459378

Catalog Description	LV AC general purpose wall-mounted drive, IEC: Pn 11 kW, 25 A, 400 V (ACS580-01-026A-4+B056)
---------------------	--

The ACS580-01 is plug-in ready to control your compressors, conveyors, pumps, extruders, centrifuges, mixers, fans and many other variable and constant torque applications, in a variety of light industries, including food and beverage, plastic, textile, material handling, and agriculture.

Long Description

All essential features are built-in as standard, simplifying drive selection, and making additional hardware unnecessary. Versatile and straightforward settings menu and assistants enable fast setup, commissioning, use and maintenance, while rugged and robust design makes it a good fit for various environments. With the ACS580 drives you can easily take full control of your processes to comprehensively manage your plant. The wall-mounted ACS580-01 comes in IP21 enclosure as standard. Also, IP55 and flange mounting units are available.

Ordering

Country of Origin	Romania (RO) Finland (FI) China (CN)
Customs Tariff Number	85044085
HS Code	850440-- Electrical transformers, static converters (for example, rectifiers) and inductors.- Static converters
Invoice Description	ACS580-01-026A-4+B056 PN: 11.0 kW, IN: 25 A
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Container Information

Gross Volume	15.388 dm ³
--------------	------------------------

Dimensions

Product Net Weight	6.8 kg 14.991 lb
Product Net Depth / Length	239.00 mm 9.409 in
Product Net Height	503 mm 19.803 in
Product Net Width	128.00 mm 5.039 in
Package Level 1 Depth / Length	225.00 mm 8.858 in
Package Level 1 Height	370.00 mm 14.567 in
Package Level 1 Width	526.00 mm 20.709 in
Package Level 1 Units	1 carton

Technical

Number of Phases	3
Degree of Protection	IP55
Enclosure Type NEMA	Type12
Altitude	1000 m 95
Sound dB (A)	64 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47.5 ... 63 Hz
Frame Size	R2
Input Voltage (U _{in})	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	CAN DeviceNet EtherNet/IP MODBUS Other Bus Systems PROFIBUS PROFINET IO

	TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6 / 3
Output Current, Heavy-Duty Use (I_{HD})	17.0 A
Output Current, Light-Overload Use (I_{LD})	23.8 A
Output Current, Normal Use (I_n)	25 A
Output Power, Heavy-Duty Use (P_{HD})	7.5 kW
Output Power, Light-Overload Use (P_{LD})	11.0 kW
Output Power, Normal Use (P_n)	11 kW
Apparent Power Output	17 kV-A
Efficiency Level	IE2
Standby Loss	15 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	126 W	87.9 %	0.7 %
0/50 %	162 W	91.6 %	0.9 %
0/100 %	284 W	92.6 %	1.6 %
50/25 %	135 W	93.4 %	0.8 %
50/50 %	180 W	95.4 %	1.0 %
50/100 %	322 W	95.8 %	1.9 %
90/50 %	196 W	97.1 %	1.1 %
90/100 %	383 W	97.2 %	2.2 %

Temperature Rating	Maximum 50 °C Minimum -15 °C
--------------------	---------------------------------

Classifications

ETIM 8	EC001857 - Frequency converter =< 1 kV
ETIM 9	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Environmental

SCIP	f016e531-e6de-4d1f-aec7-2a367861600c Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Additional Information

Product Main Type	ACS580-01
Product Name	Frequency converter

Categories

Drives → Low Voltage AC Drives → General Purpose Drives → ACS580-01 - Wall-mounted drive

