

PRODUCT-DETAILS

DRAF12-14P 250-500V50/60HZ

DRAF12-14P 250-500V50/60HZ DRAF12-14P



General Information

| | |
|-----------------------|---|
| Extended Product Type | DRAF12-14P 250-500V50/60HZ |
| Product ID | 1SBK154037R1400 |
| EAN | 3471522144942 |
| Catalog Description | DRAF12-14P 250-500V50/60HZ DRAF12-14P |
| Long Description | DRAF12-14P 250-500V50/60HZ enclosed Direct-On-Line starter with AF contactors |

Ordering

| | |
|------------------------|---------------|
| EAN | 3471522144942 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

Dimensions

| | |
|----------------------------|---------|
| Product Net Width | 107 mm |
| Product Net Height | 230 mm |
| Product Net Depth / Length | 131 mm |
| Product Net Weight | 0.82 kg |

Container Information

| | |
|-----------------------|-------------|
| Package Level 1 Units | box 1 piece |
|-----------------------|-------------|

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 243 mm |
| Package Level 1 Height | 143 mm |
| Package Level 1 Depth / Length | 112 mm |
| Package Level 1 Gross Weight | 0.82 kg |
| Package Level 1 EAN | 3471522144942 |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Additional Information

| | |
|--|---|
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP66 |
| Enclosure Class | 4x |
| Housing Material | ABS |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 1 |
| Number of Main Contacts NC | 0 |
| Number of Main Contacts NO | 3 |
| Order Multiple | 1 piece |
| Product Main Type | DRAF12 |
| Product Name | DRAF12-14P |
| Rated Operational Current AC-1 (I _e) | (690 V) 40 °C 28 A |
| Rated Operational Current AC-3 (I _e) | (380 / 400 V) 60 °C 12 A |
| Rated Operational Power AC-3 (P _e) | (380 / 400 V) 5.5 kW |
| RoHS Date | 20171115 |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|--------------------------|
| Data Sheet, Technical Information | 1SBC100199C0201 |
| Declaration of Conformity - CE | 1SBD250009U1000 |
| Instructions and Manuals | 1SBC101048M6801 |
| RoHS Information | 1SBD250009U1000 |
| UL Certificate | UL_20150729-E312527-16-1 |
| UL Listing Card | UL_E312527 |

Classifications

| | |
|---------------|--|
| ETIM 4 | EC000200 - Enclosure for control circuit devices |
| ETIM 5 | EC000200 - Enclosure for control circuit devices |
| ETIM 6 | EC000200 - Enclosure for control circuit devices |
| ETIM 7 | EC000200 - Enclosure for control circuit devices |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Control Products → Contactor Starters → Enclosed Starters

