

PRODUCT-DETAILS

SPL20/25M

25M X SPL20/BLACK CONDUIT



General Information

Extended Product Type	SPL20/25M
Product ID	7TCA296030R0140
EAN	5020963000126
Catalog Description	25M X SPL20/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963000126
Customs Tariff Number	8307106000

Dimensions

Product Net Weight	23.91 lb
	10.844 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	16 in
	406 mm

Package Level 1 Height	13 in 330 mm
Package Level 1 Depth / Length	16 in 406 mm
Package Level 2 Units	1 piece
Package Level 2 Width	16 in 406 mm
Package Level 2 Height	13 in 330 mm
Package Level 2 Depth / Length	16 in 406 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit
Radius	80 mm
UPC	786210246888

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL20/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

