

PRODUCT-DETAILS

SPL25/GR/25M

OIL RES UR LIQ.TIGHT NC25 25MT GRY



General Information

Extended Product Type	SPL25/GR/25M
Product ID	7TCA296030R0202
EAN	5020963005978
Catalog Description	OIL RES UR LIQ.TIGHT NC25 25MT GRY
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, 3/4 Inch, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Grey

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Product Type	Oil Resistant Conduit

Ordering

EAN	5020963005978
UPC	786210239460
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	25 m
----------------------------	------

Technical

Number of Batteries	0
Color	Gray
Material	Galvanized Steel Core with PVC Covering

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/GR/25M
Instructions and Manuals	SPL25/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

