



VBLST-144CW-54



Our 14.4W/m, 24V, 4000K, IP54, CRI90+ LED Strip lighting is a popular, versatile light source that will assist in creating inspiring lighting solutions. Due to being relatively inexpensive, easy to install and extremely flexible - LED strip lights are an ideal choice to enhance the mood in modern or contemporary architecture. The VIBE Range offers a huge variety of LED strip lights to choose from in different lengths, colours, and IP Ratings - with a host of accessories and aluminium extrusions to bring your design to life. Ask your VIBE Reseller about custom cut and assembly options for faster, easier installation on-site.

Features & Benefits

- High efficiency SMD LED chips
- Customisable strip suited to multiple applications
- Colour Temperature: 3000K/4000K/6000K/RGB
- IP20/IP54 rated
- 3M adhesive taper
- 120° Beam angle
- 50,000 hours lifespan
- 3 years warranty - ALL LED Strip must be installed on an aluminium heat dissipating surface for warranty purposes.



Specifications

| | |
|---------------------------------|--|
| SKU | VBLST-144CW-54 |
| Luminaire efficacy | 122.5 lm/W |
| EAN | 9340994023748 |
| Light Colour | Cool White |
| Wattage | 14.4 W |
| Lumen output | 1764 lm |
| IP rating | 54 |
| CRI | 90 |
| Beam Angle | 120 Degrees |
| Cut out | 50mm Cutting Intervals, Spaced 7.14mm mm |
| Length | 5000 mm |
| Width | 8 mm |
| Height | 2 mm |
| Lifespan | 50000 Hours |
| Warranty | 3 Years |
| Constant current/voltage | Constant Voltage |
| LED source | SMD |
| Accessories | VBLST-CTRL-BOX and VBLST-CTRL-DIM |
| Lamp Type | LED |
| Input voltage | 24 Volt DC |
| Wiring method | Fly Leads |
| Weatherproof | Weatherproof |
| Working temperature | -20°C ~ 45°C |
| Kelvin | 4000K |



Photometric information available upon request.