



## Overview

|              |   |
|--------------|---|
| Presentation | APC By Schneider Electric 6U Wall Mount is an innovative new way to deploy-server and networking equipment at the Edge. The unique low-profile design enables large depth devices to be wall mounted in a compact and less intrusive-form factor than traditional wall mount cabinets. It can ship pre-integrated with-APC Smart UPS battery backup, NetBotz Physical and Environmental Security, and EcoStruxure IT, our cloud-based remote monitoring platform to stay connected at the Edge! |
| Lead time    | Usually Ships within 2 Weeks  |

## Physical

|                            |                                       |
|----------------------------|---------------------------------------|
| Maximum mounting depth     | 76.2 Cm                               |
| Number of rack unit        | 6U                                    |
| Minimum mounting depth     | 76.2 Cm                               |
| Colour                     | Black                                 |
| Depth                      | 96.8 Cm                               |
| Rack width                 | 19"                                   |
| Height                     | 64.8 Cm                               |
| Net weight                 | 36.29 Kg                              |
| Permanent permissible load | 113.40 Kg dynamic<br>113.40 Kg static |
| Width                      | 35.3 Cm                               |

## Input

|                   |               |
|-------------------|---------------|
| Network frequency | 50 Hz         |
| Plug standard     | IEC 60320 C13 |
| Input voltage     | 230 V         |

## Conformance

|           |         |
|-----------|---------|
| Standards | UL 2416 |
|-----------|---------|

## Environmental

|          |            |
|----------|------------|
| Air flow | 103.83 L/S |
|----------|------------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

### Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 44.91 Kg |
| Package 1 Height | 42.7 Cm  |
| Package 1 width  | 106.4 Cm |
| Package 1 Length | 73.4 Cm  |

### Offer Sustainability

|                             |  |
|-----------------------------|--|
| Sustainable offer status    | Green Premium product  |
| REACH Regulation            | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC          | Yes  |
| EU RoHS Directive           | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Optimized Energy Efficiency | Energy efficient product   |
| Take-back                   | Take-back program available  |

### Contractual warranty

|          |                          |
|----------|--------------------------|
| Warranty | 5 year repair or replace |
|----------|--------------------------|

Product Life Status : **Commercialised**