



## Overview

Lead time	Usually in Stock
-----------	------------------

## General

Provided equipment	Cord retention bracket(s) Installation guide Rack mounting brackets Toolless mounting kit
--------------------	--

## Physical

Cable length	3.05 M
Colour	Black
Depth	4.4 Cm
Height	124.5 Cm
Net weight	3.07 Kg
Width	5.6 Cm

## Input

Permissible voltage	200...250 V
Max line current	10 A
Load capacity	2300 VA
Network frequency	47...63 Hz
Plug standard	IEC 60320 C14
Input voltage	200 V 208 V 230 V

## Output

Number of power socket outlets	16 IEC 60320 C13
--------------------------------	------------------

## Conformance

Product certifications	CE GOST VDE
------------------------	-------------------




## Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 M

## Packing Units

Package 1 Weight	3.98 Kg
Package 1 Height	213.4 Cm
Package 1 width	38.7 Cm
Package 1 Length	32.3 Cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : <b>Commercialised</b>
---