



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Documentation CD Installation guide Rack mounting brackets
--------------------	--

Physical

Cable length	3.05 m
Colour	Black
Depth	11.4 cm
Height	8.9 cm
Net weight	4.5 kg
Width	44.5 cm

Input

Permissible voltage	220...240 V
Input current limits	32 A
Load capacity	7360 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 32 A 2P + E
Input voltage	200 V 208 V 230 V

Output

Number of power socket outlets	16 IEC 60320 C13
--------------------------------	------------------

Conformance

Product certifications	CE GOST IRAM MIC VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	6.55 kg
Package 1 Height	14 cm
Package 1 width	50.8 cm
Package 1 Length	36.8 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------