


# PVC POWER CABLES



AUSTRALIA PACIFIC ELECTRIC CABLES

PVC Insulated, PVC Sheathed,  
Single core,  
1.0 to 16mm<sup>2</sup> 450 / 750 V to AS 5000.2

**Conductor:** annealed copper.  
**Insulation and sheath:** PVC compounds for continuous conductor temperature of 90°C.



**Standard Colours**

**Core:** Red or Black.

**Sheath:** White

Nominal conductor area mm <sup>2</sup>	Average insulation thickness mm	Approximate overall diameter mm	Approximate mass kg/100m	Product Code
1.0	0.6	4.1	2.9	VVM113
1.5	0.6	4.4	3.5	VVM105
2.5	0.7	5.2	5.2	VVM205
4.0	0.8	6.1	7.7	VVM004
6.0	0.8	6.7	10.0	VVM006
10.0	1.0	8.1	15.6	VVM010
16.0	1.0	9.3	22.7	VVM016

**Brisbane Office and Factory    Sydney Distribution Centre    Melbourne Distribution Centre    Perth Distribution Centre**

89 Platinum Street,  
Crestmead, Qld 4132  
Phone: (07) 3802 3688  
Fax: (07) 3803 6868

Unit 2, 423-427 Victoria St,  
Wetherill Park, NSW 2164  
Phone: (02) 9609 1580  
Fax: (02) 9609 1063

188 Holt Parade,  
Thomastown, VIC 3074  
Phone: (03) 9465 1188  
Fax: (03) 9465 9333

41 Banksia Road,  
Welshpool, WA 6106  
Phone: (08) 9350 1300  
Fax: (08) 9350 1333