



PVC Flexible Conduit

FEATURES:

- Highly flexible PVC conduit
- UV Resistant
- Comes with stainless steel draw wire
- Tough, durable and cost effective
- Easy to use and conveniently lightweight
- Used to effectively protect electrical wiring in underground and aboveground installations
- Manufactured to AS/NZS 2053 specifications



Temperature Range	Up to +75°C
-------------------	-------------

SPECIFICATIONS:

PART NUMBER	CONDUIT SIZE		COLOUR	LENGTH (m)	ID (MM)	OD (MM)
	mm	INCHES				
ALCDFC1615	16	3/8	Grey	15	16	21
ALCDFC1630	16	3/8	Grey	30	16	21
ALCDFC2015	20	1/2	Grey	15	20	26
ALCDFC2030	20	1/2	Grey	30	20	26
ALCDFC2515	25	3/4	Grey	15	25	33
ALCDFC2530	25	3/4	Grey	30	25	33
ALCDFC3215	32	1	Grey	15	32	42
ALCDFC3230	32	1	Grey	30	32	42
ALCDFC4010	40	1 1/2	Grey	10	40	50
ALCDFC4015	40	1 1/2	Grey	15	40	50
ALCDFC4030	40	1 1/2	Grey	30	40	50
ALCDFC5015	50	1 1/2	Grey	15	50	64
ALCDFC6315	63	2	Grey	15	63	73

Wattmaster

THE BRAND ELECTRICIANS RELY ON

T: 1300 300 747 **F:** 1300 300 074

www.wattmaster.com.au