

MR16 Reflector Downlight Kits

- Kit includes, prewired electronic transformer with lamp holder and Fire Safe thermal Cut-off, CA coil and HIH 35W = 50W lamp

HIH HALOGEN
MRE16-35-D38
Included



- **15lm/W** • 525 total lm • Dimmable
- 35Watts • 3,000K • CRI>100 • 38° Beam

LED
MR16-HPLED-WH



- **80lm/W** • 480 total lm
- 6Watts • 3,000K • CRI>80 • 38° Beam

DIECAST TILT



SVE-TLT-GD



SVE-TLT-SC



SVE-TLT-WH



SVE-TLT-SS

GLASS SHADES TO FIT SVE-TLT DOWNLIGHTS



SVE-GL-BE



SVE-GL-AC




CA 135°C □ MR16 MAX. 50W

SVE-TLT
 • Overall 83mmØ

316 Stainless Steel CA 135°C □ MR16 MAX. 50W

SVE-TLT-SS
 • Overall 80mmØ

SVE-GL-BE
 • Blue Acid glass
 • 98mmØ x 34mmH

SVE-GL-AC
 • White Acid glass
 • 98mmØ x 34mmH

Create a point of difference with an attractive glass shade accessory - provides a decorative glow on ceiling.

DIECAST FIXED



SVE-FXD-GD



SVE-FXD-SC




SVE-FXD-WH



SVE-FXD-BL

CA 135°C □ MR16 MAX. 50W

SVE-FXD
 • Overall 84mmØ

MODEL	CLASS	AIR / MOISTURE TRANSFER	INSULATION	F		CAVITY DEPTH	SIDE CLEARANCE
SVE-TLT	CA135	Closed	Side Abutted	Yes	70mm	180mm	100mm
SVE-TLT-SS	CA135	Closed	Side Abutted	Yes	70mm	180mm	100mm
SVE-FXD	CA135	Closed	Side Abutted	Yes	70mm	180mm	100mm