

# Gust

- Powerful 65W ball bearing motor for superior reliability
- High velocity airflow providing 640m³/hr extraction
- Enjoy quiet operation at just 45dB
- Draught stopper for improved energy efficiency
- Supplied with flex and plug for easy DIY installation
- 3-year return to base warranty for peace of mind



## **ORDERING INFORMATION**

**Working Temp Range** 

Order code	16764
Description	295mm 65W Ducted high velocity exhaust fan w/ round white fascia w/Light - Tri-CCT
Item Code	GUST/295/LT/WH/RD
MECHANICAL	
<b>Product Finish</b>	Matt
Fitting Colour	White
Installation Type	Recessed
IP Rating	IPx4
ELECTRICAL	
<b>Electrical Rating</b>	Class I
Input Frequency	50 Hz
Input voltage	230Vac
In Australia the Input voltage is defined as 230Vac -6%/+10% This effectively means that the voltage range of these products are 216Vac - 253Vac or 240V +6%	

-10 to 40 °C

#### **LAMP**

CCT Configuration	TRI-CCT
Colour Rendering Index (CRI)	>80

# **COLOUR TEMPERATURE**

	10 14/-44-	
	18 Watts	
	Warm White (3000 K)	1600 lm
	Cool White (4000 K)	1700 lm
	DayLight (5000 K)	1650 lm
-		

## **AIR MOVEMENT**

Outlet	150 mm
Noise level	45 dB
Motor Wattage	65 W
Motor Type	Ball bearing
Fan Type	Centrifugal
Air extraction	640 m3/hr

# **DRIVER**

Flex & Plug or Lead Length	900 mm
Wiring Type	Re-wireable Flex & Plug (3 pin)

1300 438 658 sales@evolt.com.au atomlighting.com.au © 2023 Evolt



#### **COMPLIANCE**

#### Product Design Life 10 years

The product design life relates to the total product life which includes LEDs, drivers and the enclosure. This is different to the LED lifetime which only refers to the economical lifetime of the LEDs at which time the lumen output has dropped below the L Value. The product design life is calculated at the maximum ambient or working temperature of the product and takes into account the Daily Use.

#### **Daily Use** 2 hrs

The Daily Use is the recommended time required to meet the product's design life. Installations can exceed this time, however the product design life will be reduced proportionally.

Standards	AS/NZS 60335.1
	AS/NZS 60335.2.80
	AS/NZS 60598.1
	AS/NZS 60598.2.2
	AS/NZS CISPR 14.1
	AS CISPR 15

#### **WARRANTY**

Domestic Use Warranty	3 RTB (Total 3 Years)
<b>Warranty Operating Hours</b>	2500 hrs

This product is provided with a warranty up until the stated warranty period or until the stated warranty operating hours has been reached (whichever occurs first).

#### **DIMENSIONS**

Minimum Ceiling Depth	240 mm
Cutout	295 mm
Product Height	230 mm
Product Length	320 mm
Product Width	320 mm

## **LINE DRAWINGS**

## GUST/295/LT/WH/RD

