

Group Metering Galvanised Steel



INDEX

[Leaflet](#)

[Catalogue Information](#)

WEB LINKS

[Group Metering – Galvanised Steel Information Page](#)

[Ask a question / Send us an enquiry](#)

[Information about B&R](#)

[Local Sales Team Phone Numbers](#)

Features

- Protection rating – IP23
- Removable doors
- Removable double hinged panel
- Locking facilities on door
- Padlocking kit available
- Underground service path label
- Painted and unpainted options



OVERVIEW

Providing a solution for multiple tenancy installations, Group Metering Enclosures are suitable for use in all states except Victoria, South Australia and Western Australia.



Sales in NSW supply authority regions require GMEPLK locking handle.

MATERIALS

- Body – Galvanised steel to Z275
- Body thickness – 1.2 mm
- Panel – bramite or black panel
- Surface finish – Powdercoated RAL7035



Group Metering Enclosures

SELECTION GUIDE

Product	Catalogue No.	DIN space	Dimensions (mm)			Panel (mm)					Doors
			Height	Width	Depth	Height	Width	Depth Behind	Thick	No. of panels	
Painted with DIN	JB/P	24-pole	900	600	343	560	550	150	6	1	
	JB/P/16	24-pole	900	600	420	560	550	230	6	1	
	KB/P	30-pole	900	800	343	560	750	150	6	1	
	KB/P/16	30-pole	900	800	420	560	750	230	6	1	
	LB/P	30-pole	1200	800	420	863	750	230	6	1	
	MB/P	36-pole	1200	1000	420	863	950	230	6	1	Double doors
	NB/P [▲]	30-pole	900	1600	420	560 822	750 750	230	6	2	Double doors
	OB/P [▲]	30-pole	1200	1600	420	1124 863	750 750	230	6	2	Double doors
Unpainted with DIN	JB/PU	24-pole	900	600	343	560	550	150	6	1	
	JB/PU/16	24-pole	900	600	420	560	550	230	6	1	
	KB/PU	30-pole	900	800	343	560	750	150	6	1	
	KB/PU/16	30-pole	900	800	420	560	750	230	6	1	
	LB/PU	30-pole	1200	800	420	863	750	230	6	1	
	MB/PU	36-pole	1200	1000	420	863	950	230	6	1	Double doors
	NB/PU [▲]	30-pole	900	1600	420	560 822	750 750	230	6	2	Double doors
	OB/PU [▲]	30-pole	1200	1600	420	1124 863	750 750	230	6	2	Double doors
Painted enclosures only	HB	No Din	405	432	254	385	385	230	6	1	
	IB	No Din	600	600	343	525	550	150	6	1	
	JB	No Din	900	600	343	825	550	230	6	1	
	KB	No Din	900	800	343	825	750	230	6	1	
	KB/16	No Din	900	800	420	825	750	230	6	1	
	LB	No Din	1200	800	420	1124	750	230	6	1	
	MB	No Din	1200	1000	420	1124	950	230	6	1	Double doors
	NB [▲]	No Din	900	1600	420	825	750	230	6	2	Double doors
OB [▲]	No Din	1200	1600	420	1124	750	230	6	2	Double doors	
Unpainted enclosures only	JB/U	No Din	900	600	343	825	550	230	6	1	
	JB/U/16	No Din	900	600	420	825	550	230	6	1	
	KB/U	No Din	900	800	343	825	750	230	6	1	
	KB/U/16	No Din	900	800	420	825	750	230	6	1	
	LB/U	No Din	1200	800	420	1124	750	230	6	1	
	MB/U	No Din	1200	1000	420	1124	950	230	6	1	Double doors
	NB/U [▲]	No Din	900	1600	420	825	750	230	6	2	Double doors
	OB/U [▲]	No Din	1200	1600	420	1124	750	230	6	2	Double doors

▲ Two panels supplied with product

Note: Number of meters varies depending on the state or territory. Please contact your local B&R sales representative for more information.

ACCESSORIES

A range of accessories to suit group metering enclosures.

Product	Catalogue No.	Description
Padlockable handle	GMEPLK	–
Plinths	JB/PLINTH	To suit JB
	KB/PLINTH	To suit KB/16 & LB

Queensland P +61 7 3714 1111
 Townsville P +61 7 4727 1900
 Sydney P +61 2 9915 9555
 Newcastle P +61 2 4961 4433
 Victoria P +61 3 9552 0552
 South Australia P +61 8 8417 6222

Western Australia P +61 8 6310 4777
 Tasmania P +61 3 6331 5545
 Northern Territory P +61 8 8947 0870
 sales@brenclosures.com.au
 brenclosures.com.au

