

Speaker Cable

Flexible Speaker Extension Cable



Application:

Wiring of extension speakers and power supply to electronic equipment

Benefits	
Extreme Flexibility	Class 5 flexible conductor stranding for easy installation
Easy to Install	Soft V75 PVC insulation provides increased flexibility for confined installations
Features	
✓	Fine conductor stranding for high flexing
✓	RoHS compliant to meet European environmental requirements
✓	Available in clear and gold insulation
Construction	
Conductor	Plain annealed copper wire, class 5
Insulation	V75 PVC
Colours	Clear or Gold
Ratings	
Temperature	0°C to + 75°C
Voltage	250/250V
Applicable Standards	AS/NZS1125, AS/NZS3808 , AS/NZS3191

Speaker Cable

Bambach Item Code	Conductor CSA mm ²	Conductor Stranding No. Strands/mm	Nom Ø mm	Current Rating* Amps	Weight kg/km
15500	2 x 2.64	84/0.20	4.3 x 9.2	22	89

*Current ratings based on AS/NZS 3808.1:2009 Table 4, Column 9



Flexible Conductor:
Class 5



Copper



Minimum Service
Temperature:
0°C



Maximum Service
Temperature:
75°C



Impact Resistant



Abrasion Resistant



Chemical & Oil Resistant



UV Resistant

SYDNEY (Head Office)
102 Old Pittwater Road
Brookvale NSW 2100
Phone: 02 9938 5622
Fax: 02 9938 3973

BRISBANE
2/284 Musgrave Road
Coopers Plains QLD 4108
Phone: 07 3277 5811
Fax: 07 3274 0080

MELBOURNE
9/24-26 Carrick Drive
Tullamarine VIC 3043
Phone: 03 9335 2600
Fax: 03 9330 3903

NEWCASTLE
64 Orlando Road
Lambton NSW 2299
Phone: 02 4956 2044
Fax: 02 4956 1983

WESTERN AUSTRALIA
1 Karratha St
Welshpool WA 6106
Phone: 08 9351 9966
Fax: 08 9356 2522

