

PREMIUM Exit and Emergency Luminaires

Lithium Classic Exit

Body and Diffuser sold separately.

A modular, user-friendly exit luminaire that is easily switchable between maintained and non-maintained modes of operation. The body remains the same, for both wall mounted and ceiling mounted diffuser configurations.

Features and Benefits

- Sentinel Automatic Self-testing built-in as standard
- LED technology for bright consistent & efficient light distribution
- Lithium Iron Phosphate battery including integrated battery management system (BMS) to maximize battery life.
- Wall or Ceiling Mountable
- Maintained / Non-maintained mode of operation
- Designed and manufactured in accordance to AS/NZS 2293



LiFePO₄WER™



MLEDLP (Body and Diffuser sold separately)		
Input	Operating Voltage	230V
	Frequency	50Hz
Output	Light Source	6 x 0.5W Everlight LEDs
	Function	Multi-mode
	Power Consumption	3W
Battery	Type	LiFePO ₄
	Charger	Variable current CV
	Protection	Overcharge and low voltage disconnect
	Emergency Runtime	2 hours*
Physical	IP Classification	IP20
	Weight	3.0kg
	Dimensions (LxWxH)	385x255x100mm (Body only)
	Construction	Glass-filled ABS
Installation	Mounting	Surface. Wall or Ceiling.
Environment	Temperature	0°C - 40°C
	Relative Humidity	0 - 95%
Conformance	Standards	AS/NZS 2293 / EMC
Intelligence	Sentinel	In-built
	WiNetRF	Compatible
Warranty	Duration	Fitting: 5 Years / Battery: 1 Year

*Guaranteed to meet runtime requirements of AS/NZ 2293 throughout warranty duration.

ACCESSORY	DESCRIPTION
BEL-DRX	Wall mount diffuser c/w decal pack
BEL-DTX	Ceiling mount diffuser c/w decal pack
BEL-D50A	Wall/ceiling mount translucent diffuser
BEL-901874	Wall mount wire guard
BEL-901888	Ceiling mount wire guard
BEL-31511	Replacement battery

*Exits are shipped out in maintained mode & with Sentinel option deactivated. Refer to manual for activation.

*Diffuser & body sold separately.

SPACING TABLE		MOUNTING HEIGHT (m)			
NATA Classification		2.1	2.4	2.7	3.0
MLEDLP + DRX Diffuser (Wall)					
C0 - D5 (m)		7.8	8.0	8.1	8.2
C90 - E4 (m)		6.2	6.6	7.0	7.2
MLEDLP + DTX Diffuser (Ceiling)					
C0 - D6.3 (m)		8.6	8.8	9.0	9.1
C90 - D5 (m)		7.8	8.0	8.1	8.2
MLEDLP + D50A Diffuser (Wall)					
C0 - D20 (m)		13.1	13.6	14.1	14.5
C90 - C40(m)		10.6	11.3	12.0	12.6

*Refer to AS/NZ 2293 for complete spacing table.

PREMIUM Exit and Emergency Luminaires

Classic Options - Standard Diffusers

New DRX and DTX all-in-one diffusers now complete with all variations of pictogram and exit decals.

ACCESSORY	DESCRIPTION
DRX	Wall mount diffuser c/w decal pack
DTX	Ceiling mount diffuser c/w decal pack
D50A	Wall/ceiling mount translucent emergency diffuser










Classic Options - Special Custom Diffusers

ACCESSORY	DESCRIPTION
BXA	Box style, four sided, ceiling mounted diffuser – EXIT (4 legends on each face to be specified)
RMBXA	Box style, four sided, ceiling mounted diffuser – RUNNING MAN (4 legends on each face to be specified)
DIF/SPECIAL	Other custom text screen printed diffusers



Classic Options - Low Illuminance Exit Diffusers

DESCRIPTION	PART NUMBER						
							
Wall mounted	RM1/TM	RM2/TM	RM3/TM	X1A/TM	X2A/TM	X3A/TM	X4A/TM
Ceiling mount, single side	RMX1/TM	RMX2/TM	RMX3/TM	DS1A/TM	DS2A/TM	DS3A/TM	DS4A/TM
Ceiling mount, double side	RMD1/TM	RMD2/TM	RMD2/TM	DE1A/TM	DE2A/TM	DE3A/TM	DE4A/TM