

1 3/32" x 1 3/8" Fast-acting Fuses

BBS

Specifications

Class: Supplemental

Description: Fast-acting supplementary fuse.

Dimensions: 1 3/32" x 1 3/8"
(10.3 x 34.9mm).

Construction: Fiber cartridge.

Ratings:

- Volts — 600Vac (1/10-5A)
- 250Vac (6 - 10A)
- 48Vac (12-30A)

Amps — 1/10-30A

IR — 10kA RMS Sym.

Agency Information: CE, Std. 248-14, UL Listed, 0-5A/600V, Guide JDYX, File E19180, CSA Certified, 0-5A/600V, Class 1422-01, File 53787.

Features and Benefits

- Low cost supplemental protection of non-inductive circuits
- Reduced interchangeability with other supplemental fuses minimizes misapplication

Typical Applications

- Control Circuits
- Lighting Ballasts
- Meter Circuits

Catalog Numbers (Amps)

BBS-1/10	BBS-1/20	BBS-4	BBS-15
BBS-1/20	BBS-1	BBS-5	BBS-20
BBS-1/4	BBS-1-1/2	BBS-6	BBS-25
BBS-1/10	BBS-1-1/10	BBS-7	BBS-30
BBS-1/2	BBS-1-1/20	BBS-8	
BBS-1/10	BBS-2	BBS-10	
BBS-1/4	BBS-3	BBS-12	



Recommended fuse blocks/fuse holders for 1 3/32" x 1 3/8" fuses

- Page 73

Data Sheet: 2010 (0-30A)