


Cable Tie Mounting Systems

Screw Mounts - Saddle Type

The CTB range of screw mounts are designed to securely fasten cable ties to a surface. The mounts have a two-way entry and a deep cradle design to provide extra support for large bundles and components. There are two basic sizes for standard and heavy duty ties. The bases are designed to be stronger than the tie.

Catalogue No.	H	Dimensions in mm				Standard Pack
		L	W	T	B	
Natural - Indoor Use						
CTB5NT	7	15	10	5	3	100
CTB9NT	9	23	16	9	6	100
Black - UV Resistant						
CTB5BK	7	15	10	5	3	100
CTB9BK	9	23	16	9	6	100



Cable Tie Anchors

CABAC's "Christmas Tree" anchors are a quick simple way to create an anchor point in just about any material, namely concrete, brick, wood etc. The plastic "trees" deform outwards as they are driven into the hole, creating a strong attachment. There are two basic sizes, for nominal 6mm and 9mm drill hole, and the CH9 is the same as the CH8, however with a 8mm stand off distance. Note the drill hole diameter is "nominal", since materials behave differently. It is best to trial various hole sizes for the best grip. Made from Nylon 66 and black in colour for UV resistance.

Catalogue No.	Description	Mount Hole max. (mm)	Drill Hole Diameter Nom. (mm)	Depth of Hole (mm)	Pack Size
CH5	Xmas Tree 5mm	2.4 x 6	5	30	100
LOX01B	Xmas Tree 6mm	2.4 x 10	6	30	100
CH8	Xmas Tree 9mm	3.0 x 10	8.5-9	40	50
CH9	Xmas Tree 9mm, 8mm stand off	3.0 x 10	8.5-9	40	50



Push Mounts

The CTPM1 push mount installs by snapping easily into any standard 6.4mm hole. Centring ears and locking barb design hold it securely in place. Heavy-duty spring arm compensators accommodate chassis/panel thickness up to 3.2mm and hold securely. Secures standard and light duty ties.

Catalogue No.	Base Dimensions	Dimensions (mm)		Panel Hole	Std Pack
		Height	Max Tie Width		
CTPM1/NT	7.9 x 14	17	4.8	6.3	100

