

Fibreglass Sleeving & Flex. Grommet

Fibreglass Sleeving

CABAC's Fibreglass Sleeving with silicon rubber finish is flexible, flame retardant, water repellent and recommended for high temperature applications. Easily handled and quickly applied over metallic wires for electrical and mechanical protection.

The fibreglass sleeving is made with a smooth interior and exterior finish to a wall thickness of approximately 0.45mm. The tight weave and silicone finish ensure the sleeve maintains its round shape. Available in white.

The main application of fibreglass sleeving is insulating high temperature components for home and industrial appliances such as electric heaters, toasters, stove elements, ovens, refrigerators, motors and generators.

Glass tubing is supplied in 1.2m (4ft) lengths for merchandising applications, and on reels for industrial applications.



Catalogue No.	Nominal I.D. (mm)	Length (m)	Packing Details
GS1.5	1.5	1.2	Length
GS1.5R	1.5	100	Reel
GS2.5	2.5	1.2	Length
GS2.5R	2.5	100	Reel
GS3.5	3.5	1.2	Length
GS3.5R	3.5	100	Reel
GS5	5	1.2	Length
GS5R	5	100	Reel
GS7	7	1.2	Length
GS7R	7	100	Reel
GS10	10	1.2	Length
GS10R	10	100	Reel
GS12	12	1.2	Length
GS12R	12	100	Reel

Technical Data

Conformant standards	UL file 72986
Max. operating temperature	180°C continuous
Voltage rating	415V
Breakdown voltage	1200V minimum

Flexible Grommet

CABAC's Flexible Grommet protects cables against sharp edges and abrasion on panel holes. It is supplied in 2m rolls and can be cut to length. It snaps into place and fits circular or irregular shapes.

- Material: Polyethylene
- Colour: Natural
- Max. operating temperature: 90°C

Catalogue No.	Dim (mm)	Accommodates Panel Thickness (mm)	Standard Pack (m)
FG1	1.0	Under 1.0 mm	2
FG1.6	1.6	1.0-1.6	2
FG2.4	2.4	1.6-2.4	2
FG3.2	3.2	2.4-3.2	2
FG4.5	4.5	3.2-4.5	2

