


Nylon Plugs & Rubber Grommets

Nylon Plugs - Snap In

Handy snap in Nylon Plugs that snap into a hole in a panel or chassis 0.8 to 3.2mm thick.

- Material: Nylon 66 UL, 94 V-2
- Colour: Black

Catalogue No.	Hole Size A	Chassis Thickness	Dimensions (mm)		Pack Size
			Outer Dia. B	Height C	
NP8	7.8	0.8 to 3.2	11.9	8.0	100
NP10	9.5		13.0	10.5	100
NP13	12.7		16.9	10.5	100
NP16	15.9		19.8	10.5	100
NP19	19.0		22.9	10.5	50
NP22	22.2		24.9	11.3	25
NP25	25.0		28.3	11.5	25
NP30	30.0		34.2	11.5	25
NP45	45.0		49.1	11.1	5




Flexible Rubber Grommets

Flexible Rubber Grommets, for protecting wires from sharp corners in panel and chassis holes.

- Material: Rubber
- Colour: Black

Catalogue No.	Hole Size A	Chassis Thickness	Dimensions (mm)			Pack Size
			Inner Dia. B	Outer Dia. C	Height E	
RGM6	6.0	1.7	3.0	8.3	4.7	100
RGM7	7.2	1.7	5.0	10.2	4.4	100
RGM10	10.0	1.7	6.4	13.3	6.3	100
RGM20	20.0	1.7	15.5	23.7	6.1	50
RGM25	25.0	1.5	18.9	29.9	7.2	25
RGM32	32.0	1.5	25.0	38.1	7.8	25
RGM50	Solid	1.5	-	58.0	8.0	25



Strain Relief Bushings (Grommets) - for Power Cords

CABAC's Strain Relief Bushings are designed to clamp around a cord and then are inserted into a straight sided panel hole, using an **SRBTOOL**.

Catalogue No.	Suitable for Cord Style	Dimensions (mm)					Pack Size
		Cable O.D	Panel Hole	Flat Dia. A	Max. Thick B	Length F	
SRB5P-4	Light Duty	6.4-7.4	12.7-13.1	11.5	2.5	11	25
SRB6N-4	Flexible Cables	7.6	15.9	14	1.6	14.8	25

