

HD STAINLESS STEEL BLACK JACKET

Features & Benefits

- Heavy duty, flexible 304 grade stainless steel conduit, spiral wound with corrosion resistant core
- UV stabilised black PVC jacket, superior chemical resistance
- Compression resistant to HD rating of 1250 Newtons
- Operating temperature -10 to +105 degrees Celsius, resistance to burning
- IP66 with CABFLX fittings

Ordering Information

PART NUMBER	DESCRIPTION
CSS16BK	Liquid Tight Stainless 16mm 25m
CSS20BK	Liquid Tight Stainless 20mm 25m
CSS20-150BK	Liquid Tight Stainless 20mm 150m
CSS25BK	Liquid Tight Stainless 25mm 25m
CSS25-105BK	Liquid Tight Stainless 25mm 150m
CSS32BK	Liquid Tight Stainless 32mm 25m
CSS40BK	Liquid Tight Stainless 40mm 10m
CSS50BK	Liquid Tight Stainless 50mm 10m
CSS63BK	Liquid Tight Stainless 63mm 10m



In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.