

METAL BLACK JACKET

Features & Benefits

- Extra flexible electrogalvanised steel conduit - interlocked and helically wound with PVC vacuum jacket
- UV resistant, temperature rating -20 to 70Degrees
- High mechanical protection and moisture resistance
- Suitable for tight complex bends and dynamic moving installations



Ordering Information

PART NUMBER	DESCRIPTION
CVJC10-25	Extra Flex 10mm Black 25m
CVJC12-25	Extra Flex 12mm Black 25m
CVJC16-25	Extra Flex 16mm Black 25m
CVJC20-25	Extra Flex 20mm Black 25m
CVJC25-25	Extra Flex 25mm Black 10m
CVJC32-25	Extra Flex 32mm Black 25m
CVJC40-10	Extra Flex 40mm Black 10m
CVJC50-10	Extra Flex 50mm Black 10m
CVJC63-10	Extra Flex 63mm Black 10m

PART NUMBER	NOMINAL SIZE (MM)	TRADE SIZE (INCH)	ID (MM)	OD (MM)	MIN BEND RADIUS (MM)	LENGTH (M)
CVJC10-25	10	1/4	7	10	35	25
CVJC12-25	12	5/16	10	14	43	25
CVJC16-25	16	3/8	14	17	45	25
CVJC20-25	20	1/2	17	21	58	25
CVJC25-25	25	3/4	21	26	71	25
CVJC32-25	32	1	29	34	95	25
CVJC40-10	40	1 1/4	38	44	122	10
CVJC50-10	50	1 1/2	48	55	110	10
CVJC63-10						

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.