

# LIFELIGHT-PRO

*Redefining emergency lighting*




Introducing a new benchmark in emergency lighting performance and design

The LIFELIGHT-PRO by Clevertronics offers unrivalled performance including a D50 spacing classification in an unobtrusive designer luminaire.

An amazing 60% increase in emergency lighting coverage compared with existing premium energy lights. Use less in an installation. Less than a third of the standard battery size, half the power consumption and greatly reduced materials use. All this with an unprecedented lifetime lamp warranty.

The LIFELIGHT-PRO delivers superior sustainability, maintenance and cost outcomes - all in an attractive package.



# LIFELIGHT-PRO



- D50 spacing classification, unaffected by luminaire colour.
- Superior emergency lighting coverage.
- Less required and lower installed cost.
- Lifetime lamp warranty- never need to change a lamp.
- No dome required.
- Two 85lm/W high brightness white LEDs.
- Ultra low 2.2W standby energy consumption.
- Dual-rate charging technology for longer battery life.
- Less than a third of the standard battery size.
- Square or round heads in black or white standard colours.
- Single Point, Clever-test® or Zoneworks® testing options.

## ORDERING INFORMATION

Detailed specification details including IES files available for download from the Clevertronics website.

LIFELIGHT PRO RANGE	TESTING OPTIONS			Photometrics	
	Standard	Clever-test	Zoneworks	C <sub>0</sub>	C <sub>90</sub>
<i>Standard features: Dual-rate charge, high-temp Ni-Cd batteries, lifetime lamp warranty, recessed c/w flex &amp; plug.</i>					
Recessed Round	PLIFE-PRO	DLIFE-PRO	ZLIFE-PRO	D50	D50
Recessed Round Black	PLIFE-PRO-BLK	DLIFE-PRO-BLK	ZLIFE-PRO-BLK	D50	D50
Recessed Square	PLIFE-PRO-SQ	DLIFE-PRO-SQ	ZLIFE-PRO-SQ	D50	D50
Recessed Square Black	PLIFE-PRO-SQ-BLK	DLIFE-PRO-SQ-BLK	ZLIFE-PRO-SQ-BLK	D50	D50
Surface Mounted Square	PLIFE-PRO-SMS	DLIFE-PRO-SMS	ZLIFE-PRO-SMS	D50	D50
Surface Mounted Square Black	PLIFE-PRO-SMS-BLK	DLIFE-PRO-SMS-BLK	ZLIFE-PRO-SMS-BLK	D50	D50
Surface Mounted Cylinder	PLIFE-PRO-SMC	DLIFE-PRO-SMC	ZLIFE-PRO-SMC	D50	D50
Surface Mounted Cylinder Black	PLIFE-PRO-SMC-BLK	DLIFE-PRO-SMC-BLK	ZLIFE-PRO-SMC-BLK	D50	D50

Nb: Factory standard colours are white or black, however face-plate can be removed to be painted any colour without affecting performance and AS2293 compliance. Please contact Clevertronics for information.

Small Hole Adaptor Plate	1140010	88mm Ø to suit retro-fitting into hole cut-outs up to 78mm
Large Hole Adaptor Plate	1140020	146mm Ø to suit retro-fitting into hole cut-outs up to 130mm

## SPACING TABLE

## MOUNTING HEIGHTS

Classification	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	5m	6m	7m	8m	10m	15m
D50	18.0	18.7	19.4	20.1	20.7	21.2	21.8	23.2	24.2	24.9	25.4	25.9	23.7

\*For complete spacing tables see AS2293.1



### DIMENSIONS:

Head: 60mm x 60mm (square) 60mm diameter (round)

Head depth: 50mm

Control pack: L 232mm x W 36mm x H 38mm

Battery pack: L 161mm x W 42mm x H 24mm

Hole cut-out: 51mm diameter (square and round)

This product is a REGISTERED DESIGN



Surface mounted square LIFELIGHT-PRO  
LxWxH (mm): 267 x 128 x 55



Surface mounted cylinder LIFELIGHT-PRO  
Diameter 127 (mm) x 252 Long

Please check our website for your closest Clevertronics office and local representative.

[www.clevertronics.com.au](http://www.clevertronics.com.au)

Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.