



Main

Range	Actassi
Product or component type	RJ45 network socket
Device presentation	Integrated one piece design
Colour tint	Connector: silver (zamak) Wire organizer: dark blue (ABS + PC) Connector housing: translucent (ABS + PC)
Colour code	568 A/B
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Permissible voltage	1000 V AC/DC peak, between contacts 1500 V AC/DC peak, between contacts and shield
Contact resistance	20 MOhm
Insulation resistance	Initial insulation resistance: ≥ 500 MOhm at 100 V DC
AWG gauge	AWG 23...AWG 24
Mechanical durability	750 Cycles
Coupling attenuation	≥ 45 dB at 30...100 MHz $\geq 85 - 20 \times \log(f)$ dB at 100...1000 MHz
Pin number	8 pins of copper alloy and gold plated conforming to IEC 60603-7
Protection type	Metallic: 360° self adjusting + drain wire contact Integrated short circuit barrier
Pulling force	50 N during 60 s
Transfer impedance	≤ 0.1 Ohm at 1 MHz ≤ 0.2 Ohm at 10 MHz ≤ 1.6 Ohm at 80 MHz
Transverse conversion loss	≥ 50 dB $\geq 68 - 20 \times \log(f)$ dB at 1...500000 kHz
Tool type	Punch down tool Quick termination tool
Cable outer diameter	0.9...1.4 Mm
Cable shielding type	STP
Communication network category	6A
Communication network type	10GBASE-T
Communication port protocol	VoIP (Voice IP) PoE+ (Power over Ethernet) 4PPoE 100W (Power over Ethernet)
Product compatibility	RJ45 plug RJ11 plug
Type of footprint	S-One 40 mech

Height	28 Mm
Length	35 Mm
Width	18 Mm
Targeted region	Europe Asia Pacific

Environment

Ambient air temperature for operation	-40...70 °C
Climatic withstand	40/070/21 (21 days)
Flame retardance	UL94-V0 conforming to UL listed
Environmental characteristic	REACH PEP (Energy depletion)
Product certifications	RCM
Standards	ANSI/TIA-568-C.2 AS/NZS 3080 AS/CA S008 ISO/IEC 11801 EN 50173 IEC 60603-7-51

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

Product Life Status : **Commercialised**