

Product data sheet

Characteristics

CLITPDL1C3R

Downlight, Clipsal - Lighting, 750lm, 3K/4K/6K, ripple resistant filtering, white



Main

Range	Clipsal
Product or component type	Downlight
Market segment	Residential
Main colour tint	White
Colour tint	White

Complementary

Device mounting	Ceiling
Rated power in W	7 W
Light source	LED
Total system power	230/240 V AC 50 Hz
Luminous flux	750 Lm 3000 K 750 Lm 4000 K 750 lm 6000 K
Colour rendering index	R _a =80
Bulb lifespan	50000 h
Beam angle	110 °
Trim width	110 mm
Trim height	55 mm
Cut-out dimensions	90 mm
Mounting depth	55 mm
Net weight	200 g

Environment

IP degree of protection	IP44
IK degree of protection	IK02
Insulation contact rating	IC-4
Unified glare rating	< 22

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9 cm
Package 1 Width	13 cm
Package 1 Length	13 cm
Package 1 Weight	264 g
Unit Type of Package 2	CAR
Number of Units in Package 2	24

Package 2 Height	30 cm
Package 2 Width	27.5 cm
Package 2 Length	54 cm
Package 2 Weight	6.972 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	576
Package 3 Height	110 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	188 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	3 Years
----------	---------