



Main

Range of product	Clipsal Iconic
Product or component type	Switch
Device presentation	Complete switch
Provided equipment	Screws Switch Grid plate Skin
Device application	Cooking appliances
Fixing mode	By screws
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 5
Sale per indivisible quantity	1
Rated current	45 A - 415 V AC, 50 Hz

Complementary

Device mounting	Flush
Switch function	2-pole 1-way
Number of gangs	1 gang horizontal/vertical 84 mm
Number of rocker	1
Actuator	Rocker
Surface finish	Matt
Surface treatment	Untreated
Ambient air temperature for storage	0...60 °C
Load type	Inductive
Dielectric strength	5000 V
Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Electrical durability	5000 cycles, conforming to AS/NZS 60669
Connections - terminals	6 x screw terminals
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	6 mm ² (stranded)
Wire stripping length	10 mm
Material	Skin : PC (polycarbonate) Skin : ABS (acrylonitrile butadiene-styrene) Grid plate : PC (polycarbonate) Flaps : PP (polypropylene) Housing : PC (polycarbonate) Housing : PA66
Height	120 mm
Width	78 mm
Depth	39 mm
Product weight	0.124 kg

Environment

Product certifications	RCM
------------------------	-----