



Main

| | |
|----------------------------|--------------------------|
| Range | Clipsal Iconic |
| Product or component type | Switch and socket-outlet |
| Device presentation | Grid plate with switch |
| Outlet poles configuration | 1P + E with shutter |
| Fixing mode | By screw |

Complementary

| | |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Socket number | 2 |
| Device mounting | Flush |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Ground lug position | Straight 180° position |
| Switch function | 2-way |
| Mounting mode | Horizontal |
| Colour tint | White |
| Surface finish | Matt |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |
| Sale per indivisible quantity | 1 |
| Ambient air temperature for storage | 0...60 °C |
| Rated current | 10 A for socket 10 AX for switch |
| [Ue] rated operational voltage | 250 V AC 50 Hz |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Service life in cycles | 12000 cycles |
| Electrical durability | 12000 cycles |
| Connections - terminals | Screw terminal |
| Number of terminals | 3 |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Number of cables | 1...4 |
| Clamping connection capacity | 2.5 mm ² (stranded) 2.5 mm ² (flexible) 2.5 mm ² (rigid) |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate) for grid plate PP (polypropylene) for flaps POM (polyoxymethylene) for shutter PC (polycarbonate) for switch PA66 for switch POM (polyoxymethylene) for locking bar |
| Height | 115 mm |
| Width | 71 mm |

| | |
|----------------|----------------------------------------------|
| Depth | 31 mm |
| Product weight | 0.071 kg |
| Standards | AS/NZS 3112 AS/NZS 3133 AS/NZS 60669.1 |

Environment

| | |
|------------------------|-----|
| Product certifications | RCM |
|------------------------|-----|