

Product data sheet

Characteristics

O3025-BK

Switched socket outlet, Iconic Outdoor, horizontal, Twin, 10 A, 250 V, Black



Main

| | |
|----------------------------|------------------|
| Range of product | Iconic |
| Product or component type | Switched socket |
| Product brand | Clipsal |
| Device presentation | Complete product |
| Colour | Black |
| Colour code | BK |
| Switch application | On/off switching |
| Outlet poles configuration | 1P + E |

Complementary

| | |
|--------------------------------|---|
| Control type | ON/OFF button Rocker |
| Pin number | 6 |
| Number of power socket outlets | 2 |
| Socket-outlet type | Twin switched socket-outlet |
| Fixing mode | By screws By clipping locks |
| Local signalling | Without light indicator |
| Device mounting | Surface Wall mounted |
| Mounting position | Horizontal |
| Material | PC (polycarbonate) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene) |
| Surface finish | Matt |
| Type of installation | Outdoor |
| [Ue] rated operational voltage | 250 V AC |
| Network frequency | 50 Hz |
| [In] rated current | 10 A |
| Clamping connection capacity | 4 x 2.5 mm ² 3 x 4 mm ² |
| Connections - terminals | 3 screw terminals |
| Depth | 70 mm |
| Height | 85 mm |
| Width | 115.5 mm |

Environment

| | |
|---------------------------------------|--------------|
| IP degree of protection | IP54 |
| Product certifications | RCM |
| Electrical durability | 12000 cycles |
| Ambient air temperature for storage | 0...60 °C |
| Standards | AS/NZS 3112 |
| Relative humidity | 10...95 % |
| Ambient air temperature for operation | 0...45 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 252 g |
| Package 1 Height | 8.7 cm |
| Package 1 width | 11.9 cm |
| Package 1 Length | 8.9 cm |
| Unit Type of Package 2 | BB2 |
| Number of Units in Package 2 | 30 |
| Package 2 Weight | 8.56 kg |
| Package 2 Height | 30.9 cm |
| Package 2 width | 41.3 cm |
| Package 2 Length | 45.9 cm |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 360 |
| Package 3 Weight | 111.22 kg |
| Package 3 Height | 105 cm |
| Package 3 width | 60 cm |
| Package 3 Length | 80 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Halogen content performance | Halogen free plastic parts product |