FLORYN FLA

Exterior Lighting / Flood Light

FLORYN FLA-FLA100G15K

Features

Die-cast aluminium body
Low energy consumption
Rubber supply cable
Fast turn-on, near zero maintenance
Adjustable mounting bracket

Applications

Plazas
Courtyards
Factories, warehouses
Gardens, parks
Sporting venues

Standards

Manufactured under ISO 9001:2015 to standards
IEC/AS/NZS 60598.1
IEC/AS/NZS 60598.2.5
IEC/AS/NZS CISPR 15

Mounting Methods

Trunnion

IP66 IK06 INDOOR OUTDOOR

Lighting Council AUSTRALIA MEMBER

FLORYN FLA

Exterior Lighting / Flood Light

Specifications

Model	FLA100G15K
Nominal Power (W)	100
Input Voltage (V)	220 - 240 VAC 50 / 60 Hz
Luminous Flux (lm)	9180
Efficacy (lm/W)	95
CRI (Ra)	>70
Power Factor	>0.95
CCT (K)	5000
Rated Life L70B50 (hr)	30000
Ambient Temp. ta (°C)	40
Weight (kg)	1.75

Packaging Details

Model	FLA100G15K
Product Carton Qty per box (pc)	1
Product Carton Dimension (mm)	260 x 48 x 240
Master Carton Qty per box (pc)	12
Master Carton Dimension (mm)	540 x 320 x 265
Master Carton Weight (kg)	24.5

FLORYN FLA

Exterior Lighting / Flood Light

Lighting Data



Dimensions



All photometric and electrical data published are of ±10% tolerance. Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a suitably qualified person. Application images are indicative only and may not contain actual Davis product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance.

Generated on: 04-02-2021
Copyright © 2021 Davis Lighting. All Rights Reserved.