Flush Floor Box – Flush Stainless Steel

At a glance…

- Capacity: 4 standard sized plates
- Box Size: 240 x 240 x 110mm Deep
- Features: Rubber exit flap to all 3 sides and cam lock
- Lid Material: Stainless 304 – No. 4 Linished
- Suitable for: Cat6A & 7A Cabling

"Easy as ECD"

- A lockable floor box supplied with cam lock fitted. Cam locks can be keyed alike to key number 92268 or randomly keyed.

- Flush Stainless Steel Lid and Frame with No. 4 Linished Finish.

- Rubber cable exit flaps to all three sides enables cables to safely exit the lid at any point.

- Capacity for 4 standard outlet plates (2 x double power & 2 x Data and/or A.V.).

- Suitable for category 6A and 7A data cabling with generous bend radius capacity.

- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.

- 304 Grade Solid Stainless Steel.

- Supplied with temporary construction lid.

ECD

ESTABLISHED 1979

Electric Cable Duct Systems P/L
Phone: 1300 123 ECD (323)   Fax: 1300 372 825
Email: info@ecd.net.au   website: www.ecd.net.au

ASSEMBLY DIAGRAM

FLUSH FLOOR BOX – FLUSH STAINLESS STEEL – FB4MUCL

FB4MUCL STAINLESS STEEL FLUSH LID AND FRAME ASSEMBLY WITH RUBBER CABLE EXITS TO 3 SIDES AND RECESSED LIFTING HANDLE (OVERALL LID SIZE 266 x 266)

RUBBER CABLE EXIT FLAPS TO 3 SIDES

266

266

OUTLET MOUNTING BRACKET TO SUIT 2 No. DOUBLE G.P.O.s

OUTLET MOUNTING BRACKET TO SUIT 2 No. STANDARD DATA GRID PLATES

LID SUPPORT POST

DATA PLATE VIEW

110 (INC. LID)
15
95

240

240

STEEL BOX BODY
(240 x 240 x 110mm DEEP)
12 No. 25ø/32ø COMBINATION CONDUIT KNOCKOUTS

OPTIONAL TIMBER FLOOR FIXING BRACKETS PART No. FBTFB

NOMINAL RECESS SIZE
250 x 250 x 120 DEEP FOR TIMBER FLOOR OR 300 x 300 x 120 FOAM BLOCKOUT FOR CONCRETE

110 | POWER | DATA
240 | 60

SECTION THRU' BOX

CONDUIT LOCATION BOX BASE

240
25 | 190 | 25
240
60
120
60

CONDUIT LOCATION HINGE & EXIT SIDES

15
95
70
25

240
25 | 190 | 25

TEMPORARY LID

CONDUIT LOCATION OUTLET SIDES

15
95
52
43

240
60 | 120 | 60