PROTECTOR SERIES Flush Floor Box – Flush, Square Edged, Stainless Steel

At a glance…

- **Capacity:** 4 x single auto switched power outlets and 6 x data mounts.
- **Box Size:** 240 x 240 x 70mm Deep
- **Features:** **Cable Shield**™ Frame
- **Lid Material:** Stainless 304 – No. 4 Linished
- **Suitable for:** Cat6A & 7A Cabling

"Easy as ECD"

- Flush "Protector" Series Stainless Steel Lid and Frame with No. 4 Linished Finish.
- Frame has square edges (not bevelled) to allow flush fitting to adjacent floor finish (typically timber, tiles or vinyl).
- 'Protector' Series features
  - **Cable Shield**™ Frame assembly to prevent cables being cut (Patent Pending)
  - Soft close lid to stop lid from slamming shut
  - Cable retainer for easy cable management.
- Robust and large capacity cable exit flap with retracing lifting handle.
- Capacity for 4 x single auto switched power outlets and 6 x data mounts.
- Suitable for category 6A and 7A data cabling with generous bend radius capacity.
- Suitable for Audio / Video outlets including VGA, HDMI, USB, etc.
- 304 Grade Solid Stainless Steel.
- Modular box body and lid design, interchangeable with plastic and other lids in the ECD floor box range.
- Supplied with temporary construction lid.
- Option to fit cam lock if required.

ECD
ESTABLISHED 1979

Electric Cable Duct Systems P/L
Phone: 1300 123 ECD (323)   Fax: 1300 372 825
Email: info@ecd.net.au   website: www.ecd.net.au

ABN 80005544105

JAN2015

ASSEMBLY DIAGRAM

PROTECTOR SERIES FLUSH FLOOR BOX – FLUSH, SQUARE EDGED, STAINLESS STEEL – FB4SQF70

FB4SQF SQUARE EDGE STAINLESS STEEL FLUSH LID AND FRAME ASSEMBLY WITH *CABLE SHIELD*™ FRAME, SOFT CLOSER, CABLE EXIT, RUBBER DUST SEAL AND RECESSED LIFTING HANDLE (OVERALL LID SIZE 266 x 266)

CABLE SHIELD™ FRAME ASSEMBLY

266

266

OUTLET MOUNTING BRACKET WITH PROVISION FOR 6 DATA

OUTLET MOUNTING BRACKET WITH 4 No. AUTO SWITCH G.P.O.'S

DATA PLATE VIEW

70 (INC. LID)
15
55

STEEL BOX BODY (240 x 240 x 70mm DEEP) 12 No. 25ø/32ø COMBINATION CONDUIT KNOCKOUTS

240

240

OPTIONAL TIMBER FLOOR FIXING BRACKETS PART No. FBTFB

NOMINAL RECESS SIZE 250 x 250 x 80 DEEP FOR TIMBER FLOOR OR 300 x 300 x 80 FOAM BLOCKOUT FOR CONCRETE

70

DATA   POWER

60

240

SECTION THRU' BOX

CONDUIT LOCATION BOX BASE

240
25   190   25
60
240
120
60

CONDUIT LOCATION HINGE & EXIT SIDES

240
25   190   25
15
TEMPORARY LID
55
30
25

CONDUIT LOCATION OUTLET SIDES

240
60   120   60
15
55
30
25