

Extension Leads

EMC Extension leads

10 or 15 amp 240V

Description:

10A or 15A plug and socket with insulated active/neutral pins fitted to 1.5mm² cable with tinned copper braided shield with 80% EMC coverage and extra soft triple insulated flex to avoid tangles. Approved for mining and industrial markets.

Note: 2.5mm² cable used on EXT-BRAID-30M15A



Part No.	Current (A)	Length (mtr)	Indicator
EXT-BRAID-05M10A	10	5	-
EXT-BRAID-05M10A-N	10	5	Neon
EXT-BRAID-10M10A	10	10	-
EXT-BRAID-10M10A-N	10	10	Neon
EXT-BRAID-15M10A	10	15	-
EXT-BRAID-15M10A-N	10	15	Neon
EXT-BRAID-20M10A	10	20	-
EXT-BRAID-20M10A-N	10	20	Neon
EXT-BRAID-25M10A	10	25	-
EXT-BRAID-25M10A-N	10	25	Neon
EXT-BRAID-30M10A	10	30	-
EXT-BRAID-30M10A-N	10	30	Neon
EXT-BRAID-10M15A	15	10	-
EXT-BRAID-10M15A-N	15	10	Neon
EXT-BRAID-15M15A	15	15	-
EXT-BRAID-15M15A-N	15	15	Neon
EXT-BRAID-20M15A	15	20	-
EXT-BRAID-20M15A-N	15	20	Neon
EXT-EWA-25M15A	15	25	-
EXT-BRAID-25M15A-N	15	25	Neon
EXT-BRAID-30M15A	15	30	-

IP56 EMC Extension leads

10 or 15 amp 240V

Description:

10A or 15A IP56 plug and socket with insulated active/neutral pins fitted to 1.5mm² cable with tinned copper braided shield with 80% EMC coverage and extra soft triple insulated flex to avoid tangles. Approved for mining and industrial markets.



Part No.	Current (A)	Length (mtr)
EXT-EWA56S-05M10A	10	5
EXT-EWA56S-10M10A	10	10
EXT-EWA56S-15M10A	10	15
EXT-EWA56S-20M10A	10	20
EXT-EWA56S-25M10A	10	25
EXT-EWA56S-30M10A	10	30
EXT-EWA56S-10M15A	15	10
EXT-EWA56S-15M15A	15	15
EXT-EWA56S-20M15A	15	20
EXT-EWA56S-25M15A	15	25