



Head Office:

1/13 Cooper St. Smithfield NSW 2164
P.O. Box 2084, Smithfield NSW 2164
Tel: (02) 8786 5200
Fax: (02) 8786 5288

Victoria Branch:

460-464 Hammond Rd.
Dandenong South, VIC 3175
Tel: (03) 9706 6819
Fax: (03) 9768 3580

Queensland Branch:

118 Sandstone Place
Parkinson, QLD 4115
Tel: (07) 3271 6600
Fax: (07) 3809 0411

Western Australia Branch:

24 Harrison Rd.
Forrestfield, WA 6058
Tel: (08) 9454 2628
Fax: (08) 9454 3026

Feeder cable for vehicle detectors

Standard: AS/NZS 2276.2

Conductor: Tinned Copper wire or Annealed copper wire (AS/NZS 1125)

7/0.5mm, 1.5mm²

Insulation: LDPE

Insulation Thickness: 0.5mm

Core colour: White & Black

Bedding: LDPE

Overall Screen: Aluminum tape screen, polyester mylar tape lapping and 7/0.25mm tinned copper drain wire.

Sheath: 5V-90 PVC Black

NO.	Electra Cables Part No.	No. of Pair × Cross-section mm ²	Sheath thickness mm	O/D ±10% mm	Approx. mass kg/kg
1	FD7501P	1 × 1.5	1.8	7.4	239

Note: Other types or other lengths of the above cables can be manufactured according to customers' specifications.

