



» [Construction Cables](#) » Flat TPS Cables Zero Halogen

TPS Cables - LSZH

ication:	For light to medium industrial use. For festoon systems and other applications. Suitable for all building internal wiring applications.
uctor:	Plain annealed copper (AS/NZS 1125)
ation:	X-HF-90, 90°C LSZH
th:	X-HF-90, 90°C LSZH
dard:	AS/NZS 5000.2
ing th:	100m, 500m
al ating erature:	75°C

Typical Features

Electra Cables Part No.		Stranding No./mm	Conductor area mm	Insulation Thickness mm	Sheath Thickness mm	Nom. O/D mm	Approx. Mass Kg/Km
Twin							
SRF2015VLS		7/0.50	1.5	0.6	0.9	7.4x4.7	6.2
SRF2025VLS		7/0.67	2.5	0.7	0.9	9.0x5.6	9.7
SRF2040VLS		7/0.85	4	0.8	1	10.7x6.6	14.3
SRF2060VLS		7/1.04	6	0.8	1.1	11.8x7.2	18.5
Twin + Earth							
SRF3015VLS		7/0.50	1.5	0.6	0.9	10.0x4.6	8.85
SRF3025VLS		7/0.67	2.5	0.7	1	11.7x5.3	13.7
SRF3040VLS		7/0.85	4	0.8	1.1	13.4x6.8	18.7
SRF3060VLS		7/1.04	6	0.8	1.1	14.5x6.8	23
3 Core + Earth							
SRF4015VLS		7/0.50	1.5	0.6	0.9	12.7x4.6	11.5
SRF4025VLS		7/0.67	2.5	0.7	1	14.9x5.3	18.3

Electra Cables - Sydney Office Unit 1, 13 Cooper Street Smithfield NSW 2164 Phone: (02) 8786 5200 Fax: (02) 8786 5288	Electra Cables - Melbourne Office 460-464 Hammond Road Dandenong South VIC 3175 Phone: (03) 9706 6819 Fax: (03) 9768 3580	Electra Cables - Brisbane Office 118 Sandstone Place Parkinson QLD 4115 Phone: (07) 3386 9800 Fax: (07) 3809 0411	Electra Cables -Perth Office 24 Harrison Road Forrestfield W.A 6058 Phone: (08) 9454 2628 Fax (08) 9454 3026
---	---	---	--