



Search



08 9258 8444

Cable

Motors

Dry Treat

Raychem

Heatshrink

Lugs & Terminals

Utilux

[Home](#) / [Shop Online](#) / [Cabling Accessories](#) / [Conduits](#) / [Conduit - Split Conduit](#)
[Email Us](#) [Print](#)

Shop Online



Conduit - Split Conduit

Conduit - Split Conduit (Loom Tube)

Colour: Black

Note: Used for running cable protection in
Electrical/Machinery/Building Harness wiring.
Flexible body facilitates your corner / elbow
wiring.

Material: Made from Flame Retardent Polypropylene

Operating Minimum Temperature 85.C
Temperature:

Products		Specification	Related Products			
Part No	Diamentions Inside (mm)	Diamentionas Outside (mm)	Wall Thickness (mm)	Wrapping Range (mm)	Packing Size (Metre)	
SC07PK	7.2	10.2	1.5	7.0	10	
SC07PK25	7.2	10.2	10.5	7.0	25	
SC07PK50	7.2	10.2	1.5	7.0	50	
SC11SPK	10.7	14.1	1.7	10.5	10	
SC11SPK25	10.7	14.1	1.7	10.5	25	
SC11SPK50	10.7	14.1	1.7	10.5	50	
SC13PK	13.3	17.5	2.1	13.0	10	
SC13PK25	13.3	17.5	2.1	13.0	25	
SC13PK50	13.3	17.5	2.1	13.0	50	
SC15PK	15.0	19.2	2.1	14.5	10	
SC15PK25	15.0	19.2	2.1	14.5	25	
SC15PK50	15.0	19.2	2.1	14.5	50	
SC19PK	19.3	23.5	2.1	19.0	10	
SC19PK25	19.3	23.5	2.1	19.0	25	
SC19PK50	19.3	23.5	2.1	19.0	50	
SC22PK	22.0	27.0	2.5	21.5	10	
SC22PK25	22.0	27.0	2.5	21.5	25	
SC22PK50	22.0	27.0	2.5	21.5	50	
SC28PK	28.0	34.0	3.0	27.5	10	
SC28PK25	28.0	34.0	3.0	27.5	25	
SC28PK50	28.0	34.0	3.0	27.5	50	
SC36PK	36.0	42.0	3.0	35.0	10	
SC36PK25	36.0	42.0	3.0	35.0	25	
SC48PK	48.0	54.5	3.2	47.0	10	
SC48PK25	48.0	54.5	3.2	47.0	25	

[Privacy Statement](#) [General Terms & Conditions](#) [Website Terms & Conditions of Trade](#)
Copyright © 2015 Engineering Supplies. Web by [Square18](#).