





SBLL-500 Lug-to-Lug Power Terminal – SBLL-500 (561134)



- Tinned copper block allows for copper or aluminum conductor connections
- Accessible studs allow for easy connection of sections of ERIFLEX FLEXIBAR or other conductors
- Design allows for visual inspection of conductor and confirmation of connection
- Adjustable transparent cover
- Gangable for building multi-pole power blocks
- Easily clips onto DIN rail or mounts to panel with screws
- SBLEC Power Terminals Fixing Accessory required for direct panel mount
- Halogen free
- RoHS compliant



Part Number	SBLL-500
Article Number	561134
Material	Copper Thermoplastic
Finish	Tinned
Max Current Rating, IEC	750 A
Max Current Rating, UL/CSA	475 A
Short Term Withstand Current [Icw] 1s	36 kA
Peak Short Circuit Current [Ipk]	51 kA
Short Circuit Current Rating [SCCR]	100 kA
Max Working Voltage, IEC [Ui]	1,000 VAC 1,500 VDC
Max Working Voltage, UL [Vin]	1,000 VDC
Number of Stud Connections	2
Stud Connection Conductor Width	20 – 40 mm
Stud Connection Compact Stranded Wire Size	16 – 400 mm ²
Stud Connection Wire Size	#6 - 700 kcmil
Depth [D]	65 mm
Height [H]	205.7 mm
Width [W]	85.1 mm
A	108 mm

Part Number	SBLL-500
Unit Weight	0.34 kg
Certification Details	UL® 1059
Flammability Rating	UL® 94V-1
Complies With	IEC® 60947-7-1
Certifications	cURus EAC 0234267 (Russian Federation) RoHS
Standard Packaging Quantity	1 pc
UPC	78285663095
EAN-13	8711893054019

Design Guideline for Distribution Blocks, Power Blocks and Power Terminals										
Derating according to Ambient* Temperature [°C] to maintain working temperature of 85°C										
Ambient Temperature [°C]	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°
Derating Coefficient [d]	1	1	1	0.94	0.88	0.82	0.75	0.67	0.58	0.47
*environment around the terminal blocks inside the enclosure										

Power terminal connections are interchangeable and can be used as line side or load side connections.

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair. All rights reserved.

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.