



IP40

IP67

MP, MP90 & T system

Construction: Nylon compression fittings.

Colour - black, grey on request*.

MP fitting with nylon retaining clip provides a pull off strength of 20kg with FPAS21 and IP40.

MPS fitting with a neoprene sealing ring provides a pull off strength of 15kg with FPAS21 and IP67.

FITTINGS

	IP40	IP67	IP40	IP67	IP40	IP67
	MP	MPS	MP90	MPS90	T	TS
	straight external thread	straight external thread	90° elbow external thread	90° elbow external thread	T Piece fitting	T Piece fitting with seals
	straight nylon compression fitting external thread including locknut.	Straight nylon compression fitting, with seal, external thread including locknut.	90° elbow nylon compression fitting external thread including locknut.	90° elbow nylon compression fitting, with seal, external thread including locknut.	T piece nylon compression fitting.	T piece nylon compression fitting, with seals.
						
	Ext Metric	Ext Metric	Ext Metric	Ext Metric	T Piece	T Piece

IP40
T shown

European (NW) sizes	nominal size (mm)	OD mm
7	10	10.0
7	10	
8	11	11.5
10	13	13.0
10	13	
10	13	
12	16	15.8
12	16	
12	16	
12	16	16.1
14	18	18.5
14	18	
	20	20.0
17	21	21.2
17	21	
17	21	
	25	25.0
22	25.4	25.4
23	28	28.5
23	28	
29	34	34.5
29	34	
36	42	42.5
36	42	
48	54	54.5
48	54	
56	67	67.0

ORDERING NOTES

- Metric threads supplied complete with locknuts
- Available on request:
 - reduced outlet T pieces
 - other colours
 - PG threads