

LTP, LTPHC, LTPUL & LTPE

galvanised steel, plastic coated
liquid tight

CONDUIT

LTP

Construction: Galvanised steel, helically wound, flexible conduit with smooth oil resistant and high temperature pvc cover. Colour black. Grey or orange on request.*

Typical Applications: Machine tools or outdoor installations where liquid tight is a requirement.

LTPHC

Construction: Galvanised steel, helically wound, flexible conduit with smooth thermoplastic rubber cover. Colour black.

Typical Applications: Machine tools or outdoor installations where low or high temperature rating is required. ie. food processing

LTPUL

Construction: Galvanised steel, helically wound, flexible steel conduit including copper bonding strip (up to 32mm) with smooth pvc cover. Colour black.

Typical Applications: As for LTP but where UL listing or CSA approval is required.

LTPE

Construction: Galvanised steel, helically wound, flexible conduit with smooth pvc cover. Colour black.

Typical Applications: Machine tools or outdoor installations where liquid tight is a requirement.



FITTINGS

IP66 IP67 IP68 IP69K

C

external thread nickel plated brass

Multipart compression fitting including nylon seal. Can be used for knockout or threaded entries as fitting rotates until tightened.



nominal size (mm)	US trade size (")	outside dia (mm)	inside dia (mm)	LTP part number	reel length (m)	min inside bend radius (mm)	LTPHC part number	reel length (m)	min inside bend radius (mm)	LTPUL part number	reel length (m)	min inside bend radius (mm)	LTPE part number	reel length (m)	min inside bend radius (mm)
10	1/4	11.8	7.0	LTP10B ⁺	50	35									
10															
12	3/8	14.2	10.0	LTP12B	25, 50	40	LTPHC12B	25	40						
16	1/2	17.8	12.6	LTP16B	10, 25, 50	45	LTPHC16B	25	45	LTPUL16B	25	50	LTPE16B	25	45
16															
20	3/4	21.1	16.0	LTP20B	10, 25, 50	65	LTPHC20B	25	65	LTPUL20B	25	90	LTPE20B	25	65
25	1	26.4	21.0	LTP25B	10, 25, 50	100	LTPHC25B	25	100	LTPUL25B	25	110	LTPE25B	25	100
32	1 1/4	33.1	26.5	LTP32B	10, 25	135	LTPHC32B	25	135	LTPUL32B	15	140	LTPE32B	10, 25	135
40	1 1/2	41.8	35.4	LTP40B	10, 25	175	LTPHC40B	10	175	LTPUL40B	15	180	LTPE40B*	10, 25	175
50	2	47.9	40.4	LTP50B ⁺	10, 25	230	LTPHC50B ⁺	10	230	LTPUL50B ⁺	15	230	LTPE50B*	10, 25	230
63	2 1/2	59.7	51.6	LTP63B ⁺	10, 25	280	LTPHC63B ⁺	10	280	LTPUL63B ⁺	15	280	LTPE63B*	10, 25	280

metric thread part number	PG thread part number	NPT thread part number
LTP10-M12-C		
LTP10-M16-C		
LTP12-M16-C	LTP12-PG9-C	
LTP16-M16-C	LTP16-PG11-C	
LTP16-M20-C	LTP16-PG13-C	LTP16-050-C
LTP20-M20-C	LTP20-PG16-C	LTP20-050-C
LTP25-M25-C	LTP25-PG21-C	LTP25-075-C
LTP32-M32-C	LTP32-PG29-C	LTP32-100-C
LTP40-M40-C	LTP40-PG36-C	LTP40-125-C
LTP50-M50-C	LTP50-PG42-C	
LTP63-M63-C	LTP63-PG48-C	

Note: Stainless steel fittings also available see page 29

ORDERING NOTES

- Add reel length eg: LTP20B-25M for a 25m reel
- For LTP specify colour (B = Black, G = Grey)
- * Indicates parts made to order on request and may be subject to MOQ and lead time
- + Double interlock section
- **Available on request:**
 - longer lengths and bulk packaging
 - cut lengths and assemblies
 - C-S with PG threads
 - other colours
 - internal thread fittings

How to read the fittings code

LTP20-M20-C

conduit —
thread —
fitting type —

properties

- High mechanical strength
- IP rating: IP66 + IP67 + IP68 (5 bar) + IP69K
- Smooth, wipe clean outer cover
- Cover does not wrinkle when bent
- Temperature range
 - 20°C to +105°C (LTP)
 - 45°C to +135°C (LTPHC)
 - 15°C to +75°C (LTPUL)
 - 15°C to +70°C (LTPE)
- LTP has Lloyd's Register Type Approval
- LTPUL conduits are UL listed and CSA approved
- Resistant to oils and greases (except LTPE)
- Good flexibility
- UV resistant (black) and suitable for external use
- Nickel plated brass or stainless steel fittings as shown on page 29
- Vibration and shock tested to EN61373 Cat 2



IP66 IP67 IP68 IP69K	IP66 IP67 IP68 IP69K	IP66 IP67 IP68 IP69K	IP66 IP67 IP68 IP69K	IP66 IP67 IP68 IP69K	
C-S	C90	C45	coupler	E	FCC
swivel external thread nickel plated brass Compression fitting for knockout or threaded entries. Multipart compression fitting including elastomeric seal. The external thread swivels about the main body even after tightening.	external thread nickel plated brass 90° multipart compression fitting including nylon seal. Can be used for knockout.	external thread nickel plated brass 45° multipart compression fitting including nylon seal. Can be used for knockout.	nickel plated brass Multi part compression coupler including nylon seals to join 2 conduits.	insert nickel plated brass Single part, machined insert to cap end of conduit.	plated steel P clip with pvc liner stainless steel P clips P clip to support conduit.



metric thread part number	metric thread part number	metric thread part number	part number	part number	plated steel part number	stainless steel part number	nominal size (mm)
				LTP10-E	FCC10	FCC10-SS*	10
				LTP10-E	FCC10	FCC10-SS*	10
LTP12-M16-S	LTP12-M16-C90			LTP12-E	FCC12	FCC12-SS*	12
LTP16-M16-S	LTP16-M16-C90			LTP16-E	FCC16	FCC16-SS	16
LTP16-M20-S	LTP16-M20-C90	LTP16-M20-C45		LTP16-E	FCC16	FCC16-SS	16
LTP20-M20-S	LTP20-M20-C90	LTP20-M20-C45	LTP20-LTP20	LTP20-E	FCC20	FCC20-SS	20
LTP25-M25-S	LTP25-M25-C90	LTP25-M25-C45	LTP25-LTP25	LTP25-E	FCC25	FCC25-SS	25
LTP32-M32-S	LTP32-M32-C90	LTP32-M32-C45		LTP32-E	FCC32	FCC32-SS	32
LTP40-M40-S	LTP40-M40-C90	LTP40-M40-C45		LTP40-E	FCC40	FCC40-SS	40
LTP50-M50-S	LTP50-M50-C90	LTP50-M50-C45		LTP50-E	FCC50	FCC50-SS*	50
	LTP63-M63-C90	LTP63-M63-C45		LTP63-E	FCC63		63

STANDARDS



BS EN IEC 61386



* refer to conduit properties for applicable standards

TECHNICAL DRAWING

