



GE
Lighting



Halogen Linear High Watt

TU*K4 1000W 240V R7S 189MM BX GE
1/10MIH

29181

Product information

Housing in a clear quartz bulb, these halogen floodlighting lamps have a ceramic one-pin cap on each end and can be operated on 230V or 240V mains. Linear halogen lamps provide a powerful light source for compact fittings used for floodlighting, architectural lighting and security. GE's linear halogen lamps are double ended, using the universal R7s cap format, and are available in the two industry standards of 118mm or 78mm, plus longer, higher wattage versions.

Product data

Cap/Base	R7s
Bulb Shape	Tubular
Bulb Diameter [mm]	10
Maximum Overall Length [mm]	190.5
Net weight per piece [g]	15
Gross weight per piece [g]	29
Brand	General Electric (GE)
Energy efficiency class (EEC)	D

Performance data

Colour Rendering Index (CRI) [Ra]	100
Nominal correlated colour temperature (CCT) [K]	3000
Nominal lumens [lm]	21000
Rated efficacy [lm/W]	21
Rated Life [h]	2000
Nominal power [W]	1000
Weighted energy consumption [kWh/1000h]	1018.9
Nominal lamp voltage [V]	240

Electrical data

Coil type	C-8
Dimming Capability	Yes

Logistic data

DUN Code	00043168291811
EAN Code	9004102291817
Pack Quantity	10
Layer quantity	270 EUR, 280 UK
Layer quantity EUR	270
Layer quantity UK	280
Pallet quantity EUR (PC)	4320
Pallet quantity UK (PC)	4480
Outer case size	246 x 131 x 67 (mm)
Product status	Available

Application areas



Home



Hospitality

Downloads & Links

[Go to the catalog site \(HTTP\)](#)[Halogen Lamps Spectrum Catalogue \(PDF\)](#)[Halogen DEQ and IR™ DEQ Lamps Data sheet \(PDF\)](#)[Lighting design tools & calculators \(HTTP\)](#)