



## Time switch daily cycle, 230 V, 16A, 1S

EH010

### Technical Properties

|                                       |                      |
|---------------------------------------|----------------------|
| Type of programming                   | analog               |
| Cycle                                 | daily                |
| Shortest switching time               | 15 mn                |
| Type of contacts                      | 1 changeover         |
| Rated operational AC voltage          | 210/230 V            |
| Supply failure reserve                | without              |
| Breaking capacity                     | 16A 250V AC1         |
| Max. power with incandescent lamps    | 900 W                |
| type of connection                    | with screw           |
| Number of modules                     | 1                    |
| Acceptable current rating with AC1    | 16 A                 |
| Connection cross-sect. flexible cable | 1 / 4mm <sup>2</sup> |
| Connection cross-sect. rigid cable    | 1 / 4mm <sup>2</sup> |
| Dissipated energy in cable            | 1 W                  |
| European directive RoHs               | not concerned        |
| European directive WEEE               | not concerned        |
| Fixing mode                           | Din-Rail             |
| Frequency                             | 50 Hz                |
| Number of channels                    | 1                    |
| Number of contacts                    | 1                    |
| Number of program steps               | 96                   |
| Operating temperature                 | -10 to 55 °C         |
| Storage temperature                   | -20 to 70 °C         |
| Protection index IP                   | 20                   |
| Summer / Winter time change           | manual               |
| Type of programmable thermostat       | Analogue             |