

#### Meter isolation simplified


Hager are pleased to announce the release of our meter isolator packages as a solution to assist contractors in meeting local authority requirements. Designed to be mounted on the meterbox panel, these packages come supplied within a compact Hager GD enclosure, are equipped with a single or three phase D curve circuit breaker and an engraved label for ease of identification.



# Meter isolators

# Catalogue numbers:

GD163AQ - Single phase GD363AQ - Three phase



# Specifications:

# Components GD163AQ Single phase:

- GD102T enclosure
- NDN163 D curve circuit breaker
- PFGPF10P pole filler
- Engraved self adhesive label

## GD10xT enclosure specs:

Mechanical

- IP40 with door installed

## NDN circuit breaker specs:

- Comply with AS/NZS 60898 & IEC 60947-2



#### Electrical

- D curve
- Breaking capacity 10kAVoltage rating 230/400V ACCurrent rating 63A

#### Mechanical

Connection capacity: Rigid conductor - 35mm² max. Flexible conductor - 25mm<sup>2</sup> max.

#### GD363AQ Three phase:

- GD104T enclosure
- NDN363 D curve circuit breaker
- PFGPF10P pole filler
- Engraved self adhesive label

		Enclosure size			
		Width	Height	Depth	Depth
References	Row	Α	В	С	with door
GD102T	1	55	160	80	95
GD104T	1	110	180	80	95