

IP66 isolator

Description:

The range of IP66 isolators are designed to be used in outdoor applications with IP66 degree of protection. They are rated at AC22A and AC23A offer options of 2, 3 poles and 4 poles with switched neutral. They are compact and easy to install with 2 screw quick release top cover

Electrical specification:

Tested and complies with BSEN 60947-3.

Rated voltage: 250V ~ AC
440V ~ AC

Rating **AC22A** is for switching of mixed resistive and inductive loads, including moderate overloads.

Rating **AC23A** is for switching of motor loads or other highly inductive loads.

Mechanical specification:

Protection Category: IP66

Material: Polycarbonate – UV grade.

Devices & accessories:

DP 20-40A

TP & N 20-40A

TP & SW N 20-63A



new

Description

Pack Qty.

Cat Ref.

Rating: AC22A

2 pole

20A	2 pole IP66 utility isolator	1	JG220U
32A	2 pole IP66 utility isolator	1	JG232U
40A	2 pole IP66 utility isolator	1	JG240U
63A	2 pole IP66 utility isolator	1	JG263U

3 pole

20A	2 pole IP66 utility isolator	1	JG320U
32A	2 pole IP66 utility isolator	1	JG332U
40A	2 pole IP66 utility isolator	1	JG340U

3 pole + switched neutral

20A	2 pole IP66 utility isolator	1	JG420U
32A	2 pole IP66 utility isolator	1	JG432U
40A	2 pole IP66 utility isolator	1	JG440U
63A	2 pole IP66 utility isolator	1	JG463U



upgrade

Rating: AC23A

2 pole

20A	2 pole IP66 isolator	1	JG220IN
32A	2 pole IP66 isolator	1	JG232IN
40A	2 pole IP66 isolator	1	JG240IN
63A	2 pole IP66 isolator	1	JG263IN

3 pole

20A	2 pole IP66 isolator	1	JG320IN
32A	2 pole IP66 isolator	1	JG332IN
40A	2 pole IP66 isolator	1	JG340IN

3 pole + switched neutral

20A	2 pole IP66 isolator	1	JG420IN
32A	2 pole IP66 isolator	1	JG432IN
40A	2 pole IP66 isolator	1	JG440IN
63A	2 pole IP66 isolator	1	JG463IN