



KCL368L

## Busbar MCB 3P 3R 125mm left

### Technical properties

#### Architecture

|                 |     |
|-----------------|-----|
| Number of poles | 3 P |
| Type of pole    | 3 P |

#### Compatibility

|                                        |                               |
|----------------------------------------|-------------------------------|
| Intended for the compatible references | Modular vertical distribution |
|----------------------------------------|-------------------------------|

#### Main electrical features

|                              |             |
|------------------------------|-------------|
| Rated operational voltage Ue | 110 / 415 V |
|------------------------------|-------------|

#### Voltage

|                                 |       |
|---------------------------------|-------|
| Max operating voltage           | 456 V |
| Rated impulse withstand voltage | 4 kV  |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

#### Dimensions

|        |         |
|--------|---------|
| Length | 271 mm  |
| Pitch  | 17.8 mm |

#### Power supply

|                                       |         |
|---------------------------------------|---------|
| Number of phases for the power supply | 3-phase |
|---------------------------------------|---------|

#### Materials

|        |            |
|--------|------------|
| Colour | stone grey |
|--------|------------|

#### Installation, mounting

|                                        |                         |
|----------------------------------------|-------------------------|
| Mounting way                           | vertical left hand side |
| Suitable to a device with an auxiliary | No                      |

#### Connection

|                                          |                   |
|------------------------------------------|-------------------|
| Connection cross-sect. rigid cable       | 10mm <sup>2</sup> |
| Suitable for product with neutral busbar | No                |
| Connector type                           | busbar prong      |
| Type of connection                       | -                 |

#### Cable

|                |                    |
|----------------|--------------------|
| Conductor Size | 10 mm <sup>2</sup> |
|----------------|--------------------|

#### Standards

|                         |           |
|-------------------------|-----------|
| European directive WEEE | concerned |
|-------------------------|-----------|

|                       |     |
|-----------------------|-----|
| <b>Safety</b>         |     |
| REACH conform         | Yes |
| RoHS conform          | Yes |
| <b>Use conditions</b> |     |
| Insulated             | Yes |