

## Multi-Head Outdoor, 7.1kW



Part of our Super Match range, this outdoor unit can be paired with various indoor units for a complete multi-room air conditioning solution.

- Heating and cooling, with an operational range from -15°C to 46°C
- Outdoor unit connects to up to four indoor units
- High-efficiency DC fan motor
- Indoor unit options include cassette, slim ducted and high wall models

### DIMENSIONS

Height	700mm
Width	890mm
Depth	340mm

### FEATURES & BENEFITS

#### FLEXIBLE COMBINATIONS

The Super Match range offers a wide range of possible indoor unit and outdoor unit combinations, for a customised air conditioning solution for your space.

#### DC INVERTER TECHNOLOGY

With 3D Direct Current (DC) inverter technology, Super Match air conditioning units are able to operate with a high level of energy efficiency, while delivering rapid heating and cooling as needed.

#### ANTI-CORROSION COATING

The Blue Fin coating on the evaporator is hydrophilic for quick water drainage and resistance against corrosion.

#### R32 REFRIGERANT

This Super Match outdoor unit uses a next-generation R32 refrigerant, which carries heat efficiently and has a lower Global Warming Potential than R410A.

#### FASTER SERVICING

An easily accessible maintenance panel and service screen enable fast diagnostics.

#### CENTRAL CONTROLLER

With an optional central controller, you can easily control individual or connected units, and schedule air conditioning to turn on and off automatically.

### SPECIFICATIONS

#### Capacity

Cooling capacity (kW)	7.1kW
Heating capacity (kW)	8kW

#### Consumption

COP	4.10
EER	3.64

#### Features

Blue fin coils	•
Compressor type	<b>Twin rotary</b>
DRED (Demand Response) ready	•
Inverter controlled compressor	•
MEPS approved	•
Refrigerant factory charge	<b>2.2kg</b>

#### Installation

Liquid line	<b>3x 6.35mm</b>
Maximum number indoor units	<b>3</b>
Maximum pipe run	<b>70m</b>
Suction line	<b>3x 9.52 + 1x 12.7mm</b>

#### Performance

Airflow	<b>4000m<sup>3</sup>/h</b>
DC inverter	<b>180° sine wave</b>
R32 Refrigerant	•
Sound power SWL (outdoor)	<b>68dBA</b>
Sound pressure SPL (outdoor)	<b>55dBA</b>
Working temperature cooling	<b>-10°C to +46°C</b>
Working temperature heating	<b>-15°C to +24°C</b>

#### Power requirements

AMP draw	<b>8.7A</b>
Power phase	<b>Single</b>
Supply frequency	<b>50Hz</b>

Supply voltage	<b>220-240V</b>
----------------	-----------------

---

**Product dimensions**

Depth	<b>340mm</b>
-------	--------------

Height	<b>700mm</b>
--------	--------------

Net weight	<b>61kg</b>
------------	-------------

Width	<b>890mm</b>
-------	--------------

---

**Warranty**

Parts and labour	<b>5 years</b>
------------------	----------------

---

SKU	51627
-----	-------

---

**A PEACE OF MIND SALE****24 Hours 7 Days a Week Customer Support****T 1300 729 948 W**[www.haier.com](http://www.haier.com)

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? 2020 Haier Inc. All rights reserved.