Highbays & Lowbays


HANECO

SKYLUX G5

SKYLUX120W-G5
SAP CODE: 2002421



PHOTOMETRIC DIAGRAM



Unit: cd
– C0/180 115.6deg
– C90/270 115.0deg

State-of-the-art highbay solution.

9-Highbays-in-1, the SKYLUX G5 is 3 power switchable and tritone selectable. Offering precision optics for improved performance and a tough aluminium housing with optimised heat dissipation, to ensure prolonged LED life.

APPLICATIONS

Warehouse, Storage Facilities, Manufacturing Facilities, Cool Rooms, General Industrial

KEY INFORMATION	
Power	70 W 100 W 120 W
Lumen Output	13,550 / 13,909 / 13,406 lm 16,667 / 17,298 / 16,521 lm 19,259 / 20,340 / 19,247 lm
Mounting Type	Suspended
Dimming Type	0-10V Dimmable
Body Colour	Black
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	-30 to 50°C
Connection Type	1.5m Rubber Flex & Plug
Driver	Integral
Warranty	5 yrs
PHOTOMETRIC	
Efficacy	171 / 178 / 170 lm/W 166 / 177 / 166 lm/W 161 / 175 / 162 lm/W
CCT	4000 / 5000 / 5700 K
CRI	> 80
SDCM	< 5
UGR	< 32
Beam Angle	120°
Projected Lifespan	>100,000hrs @ Ta 50°C (L70)
ELECTRICAL	
Input Voltage	100-277V, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Flicker-free	Yes
Surge Protection	Overload / Short Circuit
OTHERS	
Body Material	Die Cast Aluminium
Diffuser Material	Polycarbonate (Clear)
HACCP Approval	No
Rebate Scheme Approvals	N/A
Weight	1.8 kg
Dimensions	Ø280 x 169 mm

Specification subject to change without prior notice. Last updated 13/06/2024

HANECO

SKYLUX G5


SKYLUX120W-G5


SAP CODE: 2002421

State-of-the-art highbay solution.

9-Highbays-in-1, the SKYLUX G5 is 3 power switchable and tritone selectable. Offering precision optics for improved performance and a tough aluminium housing with optimised heat dissipation, to ensure prolonged LED life.

DIMENSIONS





120W

ACCESSORIES

Description	Product Code
Microwave Motion Sensor	SKYLUX-G5/EV-MS
Skylux120w-g5 60-degree Lens	SKYLUX120W-G5-60L
Skylux120w-g5 90-degree Lens	SKYLUX120W-G5-90L
Sensor Remote Controller	HIGHBAY-REMOTE
Surface Mount Bracket	SKYLUXG4-BRKT
Prismatic Reflector - 200W	SKYLUX200G4-PR
DALI Converter	HBAY-DALI-CONV



SKYLUX-G5/EV-MS



HIGHBAY-REMOTE



SKYLUX200G4-PR



SKYLUXG4-BRKT



HBAY-DALI-CONV

Specification subject to change without prior notice. Last updated 13/06/2024