


FLEXION RGB 5M KIT

FS75W5MRGB60-IP54

SAP CODE: 2001472



RGB, IP54, 75W, 5m
flexible, trimmable LED
strip


An RGB strip with remote control
for intensity, colour and sequence.

Accessories

DIMMABLE DRIVER



Photometric
Diagram



Unit: cd
- C0/180 125.0deg
- C90/180 125.0deg

KEY INFORMATION

Lumen Output

R: 550lm
G: 1080lm
B: 300lm
RGB: 1830lm

Input Power

75W

Dimming Options

*Phase-Cut Dimming

Trim Colour

WHITE

Warranty

5yr

IP Rating

IP54

Rebate Scheme Approvals

N/A

PHOTOMETRIC

LED

SMD

Efficacy

24.4lm/W

CCT

RGB

Beam Angle

120°

ELECTRICAL

Driver

Remote

Supply Input

220-240V, 50/60Hz

Driver Output Voltage

24VDC

Power Factor

>0.9

LED Input Current (nominal)

2800mA

Useful life @Ta25° (L70)

50,000hr

CONSTRUCTION

Fixings/Hardware

Self Adhesive Backing & Saddles

Connection Type

1.2m Flex & Plug

Total Weight

0.5kg

Dimensions

5000 x 10 x 2mm

Operating Ambient Temp.

-30 to 55°C

Electrical Classification

Class 2

Cut Length

100mm

*Dimming performance may vary depending on the specifications of the dimmer being used. For best performance use the Haneco DUO-350W dimmer.