

SKYLUX^{EVO}

SKYLUX200W-EV
SAP CODE: 2002420

Sleek and powerful.


SKYLUX EVO is a power switchable LED highbay, suitable for many commercial and industrial applications with high ceilings, and a need for high visibility and effective productivity.

APPLICATIONS

Warehouse, Storage Facilities,
Manufacturing Facilities, Cool Rooms,
General Industrial



PHOTOMETRIC DIAGRAM



Unit: cd
— C0/180 115.2deg
— C90/270 114.8deg

KEY INFORMATION

Power	100 W 150 W 170 W 200 W
Lumen Output	17,933 lm 24,455 lm 26,969 lm 29,980 lm
Mounting Type	Suspended
Dimming Type	0-10V Dimmable
Body Colour	Black
IP Rating	IP65
IK Rating	IK08
Operating Ambient Temp.	-30 to 50°C
Connection Type	1.5m Rubber Flex & Plug
Driver	Integral
Warranty	5 yrs

PHOTOMETRIC

Efficacy	174 lm/W 165 lm/W 158 lm/W 152 lm/W
CCT	5000 K
CRI	> 70
SDCM	< 5
UGR	< 32
Beam Angle	120°
Projected Lifespan	>54,000hrs @ Ta 25°C (L70)

ELECTRICAL

Input Voltage	100-277V, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Flicker-free	Yes
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Die Cast Aluminium
Diffuser Material	Polycarbonate (Clear)
HACCP Approval	No
Rebate Scheme Approvals	N/A
Weight	1.8 kg
Dimensions	Ø290 x 147 mm





SKYLUX^{EVO}

SKYLUX200W-EV
SAP CODE: 2002420

Sleek and powerful.

SKYLUX EVO is a power switchable LED highbay, suitable for many commercial and industrial applications with high ceilings, and a need for high visibility and effective productivity.

DIMENSIONS



200W

ACCESSORIES

Description	Product Code
Microwave Motion Sensor	SKYLUX-G5/EV-MS
Sensor Remote Controller	HIGHBAY-REMOTE
Surface Mount Bracket	SKYLUXG4-BRKT
Prismatic Reflector - 200W	SKYLUX200G4-PR
DALI Converter	HBAY-DALI-CONV



SKYLUX-G5/EV-MS



HIGHBAY-REMOTE



SKYLUX200G4-PR



SKYLUXG4-BRKT



HBAY-DALI-CONV