



## HENSEL IP65 Outdoor Loadcentres

**HENSEL**

### Pole

**Configuration:** 3 - 54 Poles.

### Includes:

DIN rail, top hat profile 35mm.  
Cable Entry Cover.  
Pre-moulded Metric knockout  
cable entries.

### Earth &

### Neutral Bars:

FIXCONNECT® terminal  
technology.  
Spring terminals for conductors  
up to 4mm<sup>2</sup>.  
Screw terminals for conductors  
up to 25mm<sup>2</sup>.  
Removable links for multiple  
protected neutral sections.

### Degree of protection:

IP65.  
Suitable for protected outdoor  
installation applications that is  
not in direct sunlight and indoor.  
Resistant high pressure cleaning.  
Water pressure: max 65 bar  
water temperature max 50 °C.

### Insulation voltage:

AC 400 V / DC 1000 V

### Material:

Polystyrene/Polycarbonate  
halogen-free to IEC 754-2,  
silicon-free

### Colour:

RAL7035 (Grey).

**Glow wire test:** to IEC 60 695-2-11 750°C.

### Temperature resistance:

-40 to +70°C.

### Impact

### resistance:

Mechanical resistance IK 08  
(5 Joules).



| Total<br>Poles | Configuration | Dimensions |     |     | Part No.       |
|----------------|---------------|------------|-----|-----|----------------|
|                |               | H          | W   | D   |                |
| 3              | 1 Row         | 197        | 102 | 92  | <b>KV7103</b>  |
| 4              | 1 Row         | 228        | 126 | 111 | <b>KV7104</b>  |
| 6              | 1 Row         | 238        | 146 | 111 | <b>KV7106</b>  |
| 9              | 1 Row         | 238        | 200 | 111 | <b>KV7109</b>  |
| 12             | 1 Row         | 333        | 295 | 129 | <b>KV9112M</b> |
| 18             | 1 Row         | 333        | 403 | 129 | <b>KV9118M</b> |
| 24             | 2 Rows of 12P | 458        | 295 | 129 | <b>KV9224M</b> |
| 36             | 2 Rows of 18P | 483        | 403 | 129 | <b>KV9236M</b> |
| 36             | 3 Rows of 12P | 583        | 295 | 129 | <b>KV9336M</b> |
| 48             | 4 Rows of 12P | 708        | 295 | 129 | <b>KV9448M</b> |
| 54             | 3 Rows of 18P | 630        | 403 | 129 | <b>KV9354M</b> |