



Product Code: LC18P1X18-65

IDE LC18P1X18-65 Transparent Lid With E+N Bars 18-Module 1-Row Halogen-Free Plastic RAL 7035 Grey Surface Mount IP65

- Durable polycarbonate enclosure, halogen-free
- IP65 rating for robust protection against dust & water
- Supports up to 125 A and 1500 VDC
- Surface mount with versatile cable entry options
- Transparent tinted lid for easy inspection

Specifications

Product Type	Load Centre
Brand	IDE
Ambient Temperature	-25 to 40 deg C
Ball Pressure Test	70 deg C
Cable Entry	Top, Bottom, Oblong Rear
Colour	RAL 7035 Light Grey
Degree of Protection	IP65
Depth	148 mm
Height	286 mm
Insulation Class	Class II (Double Insulation)
Lid Material	Tinted PC
Material	Halogen-Free Plastic
Mounting Type	Surface
Number of Modules	18
Number of Rows	1
Rated Current	125 A
Rated Impact Resistance	IK08
Rated Voltage	1500 VDC
Standards and Approvals	IEC 62208, Directive 2014/35/EU, AS/NZS 61439.3:2016 Appendix ZZ Clauses 10.101 and 10.102, AS/NZS 3000 Clause 2.10.4.2, IEC 62208 Directive 2014 35/EU Compliant
Weight	1.97 kg
Width	481 mm
Window Type	Transparent
Width(mm)	481

Height(mm) 286

Depth(mm) 148

Drawing

